

Cookin' with Rust

This *Rust Cookbook* is a collection of simple examples that demonstrate good practices to accomplish common programming tasks, using the crates of the Rust ecosystem.

[Read more about *Rust Cookbook*](#), including tips for how to read the book, how to use the examples, and notes on conventions.

Contributing

This project is intended to be easy for new Rust programmers to contribute to, and an easy way to get involved with the Rust community. It needs and welcomes help. For details see [CONTRIBUTING.md](#).

Algorithms

| Recipe | Crates | Categories |
|---|-------------|------------|
| Generate random numbers | rand v0.7.3 | Science |
| Generate random numbers within a range | rand v0.7.3 | Science |
| Generate random numbers with given distribution | rand v0.7.3 | Science |
| Generate random values of a custom type | rand v0.7.3 | Science |
| Create random passwords from a set of alphanumeric characters | rand v0.7.3 | OS |
| Create random passwords from a set of user-defined characters | rand v0.7.3 | OS |
| Sort a Vector of Integers | std 1.29.1 | Science |
| Sort a Vector of Floats | std 1.29.1 | Science |
| Sort a Vector of Structs | std 1.29.1 | Science |

Command Line

| Recipe | Crates | Categories |
|------------------------------|-------------------|--------------|
| Parse command line arguments | clap v2.33.0 | Command line |
| ANSI Terminal | ansi_term v0.11.0 | Command line |

Compression

| Recipe | Crates | Categories |
|---|-------------------------------|-------------|
| Decompress a tarball | flate2 v1.0.13 tar v0.4.26 | Compression |
| Compress a directory into a tarball | flate2 v1.0.13 tar v0.4.26 | Compression |
| Decompress a tarball while removing a prefix from the paths | flate2 v1.0.13 tar v0.4.26 | Compression |

Concurrency

| Recipe | Crates | Categories |
|---|--|-------------------------------------|
| Spawn a short-lived thread | crossbeam v0.7.3 | Concurrency |
| Pass data between two threads | crossbeam v0.7.3 | Concurrency |
| Maintain global mutable state | lazy_static v1.4.0 | Rust patterns |
| Calculate SHA1 sum of *.iso files concurrently | threadpool v1.7.1 walkdir v2.3.1 num_cpus v1.12.0 ring v0.16.10 | Concurrency Filesystem |
| Draw fractal dispatching work to a thread pool | threadpool v1.7.1 num v0.2.1 num_cpus v1.12.0 image v0.23.0-preview.0 | Concurrency Science Rendering |
| Mutate the elements of an array in parallel | rayon v1.3.0 | Concurrency |
| Test in parallel if any or all elements of a collection match a given predicate | rayon v1.3.0 | Concurrency |
| Search items using given predicate in parallel | rayon v1.3.0 | Concurrency |

| Recipe | Crates | Categories |
|-------------------------------------|--|---------------------------|
| Sort a vector in parallel | rayon v1.3.0 rand v0.7.3 | Concurrency |
| Map-reduce in parallel | rayon v1.3.0 | Concurrency |
| Generate jpg thumbnails in parallel | rayon v1.3.0 glob v0.3.0 image v0.23.0-preview.0 | Concurrency Filesystem |

Cryptography

| Recipe | Crates | Categories |
|---|---------------------------------------|--------------|
| Calculate the SHA-256 digest of a file | ring v0.16.10 data-encoding v2.1.2 | Cryptography |
| Sign and verify a message with an HMAC digest | ring v0.16.10 | Cryptography |
| Salt and hash a password with PBKDF2 | ring v0.16.10 data-encoding v2.1.2 | Cryptography |

Data Structures

| Recipe | Crates | Categories |
|--|-----------------|------------|
| Define and operate on a type represented as a bitfield | bitflags v1.2.1 | No std |

Database

| Recipe | Crates | Categories |
|--------------------------------------|------------------|------------|
| Create a SQLite database | rusqlite v0.21.0 | Database |
| Insert and Query data | rusqlite v0.21.0 | Database |
| Create tables in a Postgres database | postgres v0.17.1 | Database |
| Insert and Query data | postgres v0.17.1 | Database |
| Aggregate data | postgres v0.17.1 | Database |

Date and Time

| Recipe | Crates | Categories |
|---|----------------|---------------|
| Measure elapsed time | std 1.29.1 | Time |
| Perform checked date and time calculations | chrono v0.4.10 | Date and time |
| Convert a local time to another timezone | chrono v0.4.10 | Date and time |
| Examine the date and time | chrono v0.4.10 | Date and time |
| Convert date to UNIX timestamp and vice versa | chrono v0.4.10 | Date and time |
| Display formatted date and time | chrono v0.4.10 | Date and time |
| Parse string into DateTime struct | chrono v0.4.10 | Date and time |

Development Tools

Debugging

| Recipe | Crates | Categories |
|---|---------------------------------|------------|
| Log a debug message to the console | log v0.4.8 env_logger v0.7.1 | Debugging |
| Log an error message to the console | log v0.4.8 env_logger v0.7.1 | Debugging |
| Log to stdout instead of stderr | log v0.4.8 env_logger v0.7.1 | Debugging |
| Log messages with a custom logger | log v0.4.8 | Debugging |
| Log to the Unix syslog | log v0.4.8 syslog v5.0.0 | Debugging |
| Enable log levels per module | log v0.4.8 env_logger v0.7.1 | Debugging |
| Use a custom environment variable to set up logging | log v0.4.8 env_logger v0.7.1 | Debugging |

| Recipe | Crates | Categories |
|-----------------------------------|---|------------|
| Include timestamp in log messages | log v0.4.8 env_logger v0.7.1 chrono v0.4.10 | Debugging |
| Log messages to a custom location | log v0.4.8 log4rs v0.10.0 | Debugging |

Versioning

| Recipe | Crates | Categories |
|--|---------------|-----------------------|
| Parse and increment a version string | semver v0.9.0 | Config |
| Parse a complex version string | semver v0.9.0 | Config |
| Check if given version is pre-release | semver v0.9.0 | Config |
| Find the latest version satisfying given range | semver v0.9.0 | Config |
| Check external command version for compatibility | semver v0.9.0 | Text processing OS |

Build Time

| Recipe | Crates | Categories |
|--|------------|-------------------|
| Compile and link statically to a bundled C library | cc v1.0.50 | Development tools |
| Compile and link statically to a bundled C++ library | cc v1.0.50 | Development tools |
| Compile a C library while setting custom defines | cc v1.0.50 | Development tools |

Encoding

| Recipe | Crates | Categories |
|-------------------------|------------|------------|
| Percent-encode a string | url v2.1.1 | Encoding |

| Recipe | Crates | Categories |
|--|------------------------------|------------|
| Encode a string as application/x-www-form-urlencoded | url v2.1.1 | Encoding |
| Encode and decode hex | data-encoding v2.1.2 | Encoding |
| Encode and decode base64 | base64 v0.11.0 | Encoding |
| Read CSV records | csv v1.1.3 | Encoding |
| Read CSV records with different delimiter | csv v1.1.3 | Encoding |
| Filter CSV records matching a predicate | csv v1.1.3 | Encoding |
| Handle invalid CSV data with Serde | csv v1.1.3 serde v1.0.104 | Encoding |
| Serialize records to CSV | csv v1.1.3 | Encoding |
| Serialize records to CSV using Serde | csv v1.1.3 serde v1.0.104 | Encoding |
| Transform one column of a CSV file | csv v1.1.3 serde v1.0.104 | Encoding |
| Serialize and deserialize unstructured JSON | serde_json v1.0.45 | Encoding |
| Deserialize a TOML configuration file | toml v0.5.6 | Encoding |
| Read and write integers in little-endian byte order | byteorder v1.3.2 | Encoding |

File System

| Recipe | Crates | Categories |
|---|------------------|------------------|
| Read lines of strings from a file | std 1.29.1 | Filesystem |
| Avoid writing and reading from a same file | same_file v1.0.6 | Filesystem |
| Access a file randomly using a memory map | memmap v0.7.0 | Filesystem |
| File names that have been modified in the last 24 hours | std 1.29.1 | Filesystem OS |
| Find loops for a given path | same_file v1.0.6 | Filesystem |
| Recursively find duplicate file names | walkdir v2.3.1 | Filesystem |
| Recursively find all files with given predicate | walkdir v2.3.1 | Filesystem |

| Recipe | Crates | Categories |
|--|----------------|------------|
| Traverse directories while skipping dotfiles | walkdir v2.3.1 | Filesystem |
| Recursively calculate file sizes at given depth | walkdir v2.3.1 | Filesystem |
| Find all png files recursively | glob v0.3.0 | Filesystem |
| Find all files with given pattern ignoring filename case | glob v0.3.0 | Filesystem |

Hardware Support

| Recipe | Crates | Categories |
|-----------------------------------|------------------|------------------|
| Check number of logical cpu cores | num_cpus v1.12.0 | Hardware support |

Memory Management

| Recipe | Crates | Categories |
|-----------------------------------|--------------------|--------------------------|
| Declare lazily evaluated constant | lazy_static v1.4.0 | Caching Rust patterns |

Networking

| Recipe | Crates | Categories |
|------------------------------|------------|------------|
| Listen on unused port TCP/IP | std 1.29.1 | Net |

Operating System

| Recipe | Crates | Categories |
|--|--------------|-----------------------|
| Run an external command and process stdout | regex v1.3.4 | OS Text processing |
| Run an external command passing it stdin and check for an error code | regex v1.3.4 | OS Text processing |
| Run piped external commands | std 1.29.1 | OS |

| Recipe | Crates | Categories |
|---|------------|-----------------------|
| Redirect both stdout and stderr of child process to the same file | std 1.29.1 | OS |
| Continuously process child process' outputs | std 1.29.1 | OS Text processing |

Science

Mathematics

| Recipe | Crates | Categories |
|---|------------------|------------|
| Vector Sum | ndarray v0.13.0 | Science |
| Vector Norm | ndarray v0.13.0 | Science |
| Adding matrices | ndarray v0.13.0 | Science |
| Multiplying matrices | ndarray v0.13.0 | Science |
| Multiply a scalar with a vector with a matrix | ndarray v0.13.0 | Science |
| Invert marix | nalgebra v0.19.0 | Science |
| Calculating the side length of a triangle | std 1.29.1 | Science |
| Verifying tan is equal to sin divided by cos | std 1.29.1 | Science |
| Distance between two points on the Earth | std 1.29.1 | Science |
| Creating complex numbers | num v0.2.1 | Science |
| Adding complex numbers | num v0.2.1 | Science |
| Mathematical functions on complex numbers | num v0.2.1 | Science |
| Measures of central tendency | std 1.29.1 | Science |
| Computing standard deviation | std 1.29.1 | Science |
| Big integers | num v0.2.1 | Science |

Text Processing

| Recipe | Crates | Categories |
|--------|--------|------------|
|--------|--------|------------|

| Recipe | Crates | Categories |
|---|------------------------------------|-----------------|
| Collect Unicode Graphemes | unicode-segmentation v1.6.0 | Encoding |
| Verify and extract login from an email address | regex v1.3.4 lazy_static v1.4.0 | Text processing |
| Extract a list of unique #Hashtags from a text | regex v1.3.4 lazy_static v1.4.0 | Text processing |
| Extract phone numbers from text | regex v1.3.4 | Text processing |
| Filter a log file by matching multiple regular expressions | regex v1.3.4 | Text processing |
| Replace all occurrences of one text pattern with another pattern. | regex v1.3.4 lazy_static v1.4.0 | Text processing |
| Implement the <code>FromStr</code> trait for a custom struct | std 1.29.1 | Text processing |

Web Programming

Scraping Web Pages

| Recipe | Crates | Categories |
|--|--|------------|
| Extract all links from a webpage HTML | reqwest v0.10.1 select v0.4.3 | Net |
| Check webpage for broken links | reqwest v0.10.1 select v0.4.3 url v2.1.1 | Net |
| Extract all unique links from a MediaWiki markup | reqwest v0.10.1 regex v1.3.4 | Net |

Uniform Resource Locations (URL)

| Recipe | Crates | Categories |
|--------|--------|------------|
|--------|--------|------------|

| Recipe | Crates | Categories |
|--|-------------------------|------------|
| Parse a URL from a string to a <code>url</code> type | <code>url</code> v2.1.1 | Net |
| Create a base URL by removing path segments | <code>url</code> v2.1.1 | Net |
| Create new URLs from a base URL | <code>url</code> v2.1.1 | Net |
| Extract the URL origin (scheme / host / port) | <code>url</code> v2.1.1 | Net |
| Remove fragment identifiers and query pairs from a URL | <code>url</code> v2.1.1 | Net |

Media Types (MIME)

| Recipe | Crates | Categories |
|--|--|-----------------|
| Get MIME type from string | <code>mime</code> v1.1.3 | Encoding |
| Get MIME type from filename | <code>mime</code> v1.1.3 | Encoding |
| Parse the MIME type of a HTTP response | <code>mime</code> v1.1.3 <code>request</code> v0.10.1 | Net Encoding |

Clients

| Recipe | Crates | Categories |
|--|---|-------------------|
| Make a HTTP GET request | <code>request</code> v0.10.1 | Net |
| Query the GitHub API | <code>request</code> v0.10.1 <code>serde</code> v1.0.104 | Net Encoding |
| Check if an API resource exists | <code>request</code> v0.10.1 | Net |
| Create and delete Gist with GitHub API | <code>request</code> v0.10.1 <code>serde</code> v1.0.104 | Net Encoding |
| Consume a paginated RESTful API | <code>request</code> v0.10.1 <code>serde</code> v1.0.104 | Net Encoding |
| Download a file to a temporary directory | <code>request</code> v0.10.1 <code>tempdir</code> v0.3.7 | Net Filesystem |

| Recipe | Crates | Categories |
|---|---|------------------|
| Make a partial download with HTTP range headers | <code>request</code> <code>v0.10.1</code> | <code>Net</code> |
| POST a file to paste-rs | <code>request</code> <code>v0.10.1</code> | <code>Net</code> |

About "Cookin' with Rust"

Table of contents

- [Who this book is for](#)
- [How to read this book](#)
- [How to use the recipes](#)
- [A note about error handling](#)
- [A note about crate representation](#)

Who this book is for

This cookbook is intended for new Rust programmers, so that they may quickly get an overview of the capabilities of the Rust crate ecosystem. It is also intended for experienced Rust programmers, who should find in the recipes an easy reminder of how to accomplish common tasks.

How to read this book

The cookbook [index](#) contains the full list of recipes, organized into a number of sections: "basics", "encoding", "concurrency", etc. The sections themselves are more or less ordered in progression, with later sections being more advanced, and occasionally building on concepts from earlier sections.

Within the index, each section contains a list of recipes. The recipes are simple statements of a task to accomplish, like "generate random numbers in a range"; and each recipe is tagged with badges indicating which *crates* they use, like

`rand` `v0.7.3`, and which categories on [crates.io](#) those crates belong to, like `Science`.

New Rust programmers should be comfortable reading from the first section to the last, and doing so should give one a strong overview of the crate ecosystem. Click on the section header in the index, or in the sidebar to navigate to the page for that section of the book.

If you are simply looking for the solution to a simple task, the cookbook is today more difficult to navigate. The easiest way to find a specific recipe is to scan the index looking for the crates and categories one is interested in. From there, click on the name of the recipe to view it. This will improve in the future.

How to use the recipes

Recipes are designed to give you instant access to working code, along with a full explanation of what it is doing, and to guide you to further information.

All recipes in the cookbook are full, self contained programs, so that they may be copied directly into your own projects for experimentation. To do so follow the instructions below.

Consider this example for "generate random numbers within a range":

`rand` `v0.7.3` `Science`

```
extern crate rand;
use rand::Rng;

fn main() {
    let mut rng = rand::thread_rng();
    println!("Random f64: {}", rng.gen::<f64>());
}
```

To work with it locally we can run the following commands to create a new cargo project, and change to that directory:

```
cargo new my-example --bin
cd my-example
```

Now, we also need to add the necessary crates to [Cargo.toml](#), as indicated by the crate badges, in this case just "rand". To do so, we'll use the `cargo add` command, which is provided by the `cargo-edit` crate, which we need to install first:

```
cargo install cargo-edit
cargo add rand
```

Now you can replace `src/main.rs` with the full contents of the example and run it:

```
cargo run
```

The crate badges that accompany the examples link to the crates' full documentation on docs.rs, and is often the next documentation you should read after deciding which crate suites your purpose.

A note about error handling

Error handling in Rust is robust when done correctly, but in today's Rust it requires a fair bit of boilerplate. Because of this one often sees Rust examples filled with `unwrap` calls instead of proper error handling.

Since these recipes are intended to be reused as-is and encourage best practices, they set up error handling correctly when there are `Result` types involved.

The basic pattern we use is to have a `fn main() -> Result`.

The structure generally looks like:

```

#[macro_use]
extern crate error_chain;

use std::net::IpAddr;
use std::str;

error_chain! {
    foreign_links {
        Utf8(std::str::Utf8Error);
        AddrParse(std::net::AddrParseError);
    }
}

fn main() -> Result<()> {
    let bytes = b"2001:db8::1";

    // Bytes to string.
    let s = str::from_utf8(bytes)?;

    // String to IP address.
    let addr: IpAddr = s.parse()?;

    println!("{:?}", addr);
    Ok(())
}

```

This is using the `error_chain!` macro to define a custom `Error` and `Result` type, along with automatic conversions from two standard library error types. The automatic conversions make the `?` operator work.

For the sake of readability error handling boilerplate is hidden by default like below. In order to read full contents click on the "expand" () button located in the top right corner of the snippet.

```

extern crate url;

use url::{Url, Position};

fn main() -> Result<()> {
    let parsed = Url::parse("https://httpbin.org/cookies/set?k2=v2&k1=v1")?;
    let cleaned: &str = &parsed[..Position::AfterPath];
    println!("cleaned: {}", cleaned);
    Ok(())
}

```

For more background on error handling in Rust, read [this page of the Rust book](#)

and [this blog post](#).

A note about crate representation

This cookbook is intended eventually to provide expansive coverage of the Rust crate ecosystem, but today is limited in scope while we get it bootstrapped and work on the presentation. Hopefully, starting from a small scope and slowly expanding will help the cookbook become a high-quality resource sooner, and allow it to maintain consistent quality levels as it grows.

At present the cookbook is focused on the standard library, and on "core", or "foundational", crates—those crates that make up the most common programming tasks, and that the rest of the ecosystem builds off of.

The cookbook is closely tied to the [Rust Libz Blitz](#), a project to identify, and improve the quality of such crates, and so it largely defers crate selection to that project. Any crates that have already been evaluated as part of that process are in scope for the cookbook, as are crates that are pending evaluation.

Algorithms

| Recipe | Crates | Categories |
|---|-------------|------------|
| Generate random numbers | rand v0.7.3 | Science |
| Generate random numbers within a range | rand v0.7.3 | Science |
| Generate random numbers with given distribution | rand v0.7.3 | Science |
| Generate random values of a custom type | rand v0.7.3 | Science |
| Create random passwords from a set of alphanumeric characters | rand v0.7.3 | OS |
| Create random passwords from a set of user-defined characters | rand v0.7.3 | OS |
| Sort a Vector of Integers | std 1.29.1 | Science |
| Sort a Vector of Floats | std 1.29.1 | Science |
| Sort a Vector of Structs | std 1.29.1 | Science |

Generate Random Values

Generate random numbers

rand v0.7.3 Science

Generates random numbers with help of random-number generator `rand::Rng` obtained via `rand::thread_rng`. Each thread has an initialized generator. Integers are uniformly distributed over the range of the type, and floating point numbers are uniformly distributed from 0 up to but not including 1.

```
extern crate rand;

use rand::Rng;

fn main() {
    let mut rng = rand::thread_rng();

    let n1: u8 = rng.gen();
    let n2: u16 = rng.gen();
    println!("Random u8: {}", n1);
    println!("Random u16: {}", n2);
    println!("Random u32: {}", rng.gen::());
    println!("Random i32: {}", rng.gen::());
    println!("Random float: {}", rng.gen::());
}
```

Generate random numbers within a range

rand v0.7.3 Science

Generates a random value within half-open $[0, 10)$ range (not including 10) with `Rng::gen_range`.

```
extern crate rand;

use rand::Rng;

fn main() {
    let mut rng = rand::thread_rng();
    println!("Integer: {}", rng.gen_range(0, 10));
    println!("Float: {}", rng.gen_range(0.0, 10.0));
}
```

`Uniform` can obtain values with [uniform distribution](#). This has the same effect, but may be faster when repeatedly generating numbers in the same range.

```
extern crate rand;

use rand::distributions::{Distribution, Uniform};

fn main() {
    let mut rng = rand::thread_rng();
    let die = Uniform::from(1..7);

    loop {
        let throw = die.sample(&mut rng);
        println!("Roll the die: {}", throw);
        if throw == 6 {
            break;
        }
    }
}
```

Generate random numbers with given distribution

rand v0.7.3 Science

By default, random numbers have [uniform distribution](#). To generate numbers with other distributions you instantiate a distribution, then sample from that distribution using `Distribution::sample` with help of a random-number generator `rand::Rng`.

The [distributions available](#) are documented here. An example using the `Normal` distribution is shown below.

```
extern crate rand;

use rand::distributions::{Normal, Distribution};

fn main() {
    let mut rng = rand::thread_rng();
    let normal = Normal::new(2.0, 3.0);
    let v = normal.sample(&mut rng);
    println!("{}", v);
}
```

Generate random values of a custom type

rand v0.7.3 Science

Randomly generates a tuple `(i32, bool, f64)` and variable of user defined type `Point`. Implements the `Distribution` trait on type `Point` for `Standard` in order to allow random generation.

```
extern crate rand;

use rand::Rng;
use rand::distributions::{Distribution, Standard};

#[derive(Debug)]
struct Point {
    x: i32,
    y: i32,
}

impl Distribution<Point> for Standard {
    fn sample<R: Rng + ?Sized>(&self, rng: &mut R) -> Point {
        let (rand_x, rand_y) = rng.gen();
        Point {
            x: rand_x,
            y: rand_y,
        }
    }
}

fn main() {
    let mut rng = rand::thread_rng();
    let rand_tuple = rng.gen:::<(i32, bool, f64)>();
    let rand_point: Point = rng.gen();
    println!("Random tuple: {:?}", rand_tuple);
    println!("Random Point: {:?}", rand_point);
}
```

Create random passwords from a set of alphanumeric characters

rand v0.7.3 OS

Randomly generates a string of given length ASCII characters in the range A-Z, a-z, 0-9, with `Alphanumeric` sample.

```
extern crate rand;

use rand::{thread_rng, Rng};
use rand::distributions::Alphanumeric;

fn main() {
    let rand_string: String = thread_rng()
        .sample_iter(&Alphanumeric)
        .take(30)
        .collect();

    println!("{}", rand_string);
}
```

Create random passwords from a set of user-defined characters

rand v0.7.3 OS

Randomly generates a string of given length ASCII characters with custom user-defined bytestring, with `gen_range`.

```
extern crate rand;

fn main() {
    use rand::Rng;
    const CHARSET: &[u8] = b"ABCDEFGHJKLMNOPQRSTUVWXYZ\
                           abcdefghijklmnopqrstuvwxyz\
                           0123456789)(*^%$#@!~";

    const PASSWORD_LEN: usize = 30;
    let mut rng = rand::thread_rng();

    let password: String = (0..PASSWORD_LEN)
        .map(|_| {
            let idx = rng.gen_range(0, CHARSET.len());
            CHARSET[idx] as char
        })
        .collect();

    println!("{:?}", password);
}
```

Sorting Vectors

Sort a Vector of Integers

std 1.29.1 Science

This example sorts a Vector of integers via `vec::sort`. Alternative would be to use `vec::sort_unstable` which can be faster, but does not preserve the order of equal elements.

```
fn main() {
    let mut vec = vec![1, 5, 10, 2, 15];

    vec.sort();

    assert_eq!(vec, vec![1, 2, 5, 10, 15]);
}
```

Sort a Vector of Floats

std 1.29.1 Science

A Vector of f32 or f64 can be sorted with `vec::sort_by` and `PartialOrd::partial_cmp`.

```
fn main() {
    let mut vec = vec![1.1, 1.15, 5.5, 1.123, 2.0];

    vec.sort_by(|a, b| a.partial_cmp(b).unwrap());

    assert_eq!(vec, vec![1.1, 1.123, 1.15, 2.0, 5.5]);
}
```

Sort a Vector of Structs

std 1.29.1 Science

Sorts a Vector of Person structs with properties `name` and `age` by its natural order (By name and age). In order to make Person sortable you need four traits `Eq`, `PartialEq`, `Ord` and `PartialOrd`. These traits can be simply derived. You can also provide a custom comparator function using a `vec::sort_by` method and sort only

by age.

```
#[derive(Debug, Eq, Ord, PartialEq, PartialOrd)]
struct Person {
    name: String,
    age: u32
}

impl Person {
    pub fn new(name: String, age: u32) -> Self {
        Person {
            name,
            age
        }
    }
}

fn main() {
    let mut people = vec![
        Person::new("Zoe".to_string(), 25),
        Person::new("Al".to_string(), 60),
        Person::new("John".to_string(), 1),
    ];

    // Sort people by derived natural order (Name and age)
    people.sort();

    assert_eq!(
        people,
        vec![
            Person::new("Al".to_string(), 60),
            Person::new("John".to_string(), 1),
            Person::new("Zoe".to_string(), 25),
        ]
    );

    // Sort people by age
    people.sort_by(|a, b| b.age.cmp(&a.age));

    assert_eq!(
        people,
        vec![
            Person::new("Al".to_string(), 60),
            Person::new("Zoe".to_string(), 25),
            Person::new("John".to_string(), 1),
        ]
    );
}
```

Command Line

| Recipe | Crates | Categories |
|--|-------------------|--------------|
| Parse command line arguments | clap v2.33.0 | Command line |
| ANSI Terminal | ansi_term v0.11.0 | Command line |

Clap basic

Parse command line arguments

clap v2.33.0 [Command line](#)

This application describes the structure of its command-line interface using `clap`'s builder style. The [documentation](#) gives two other possible ways to instantiate an application.

In the builder style, `with_name` is the unique identifier that `value_of` will use to retrieve the value passed. The `short` and `long` options control the flag the user will be expected to type; short flags look like `-f` and long flags look like `--file`.

```

extern crate clap;

use clap::{Arg, App};

fn main() {
    let matches = App::new("My Test Program")
        .version("0.1.0")
        .author("Hackerman Jones <hckrmnjones@hack.gov>")
        .about("Teaches argument parsing")
        .arg(Arg::with_name("file")
            .short("f")
            .long("file")
            .takes_value(true)
            .help("A cool file"))
        .arg(Arg::with_name("num")
            .short("n")
            .long("number")
            .takes_value(true)
            .help("Five less than your favorite number"))
        .get_matches();

    let myfile = matches.value_of("file").unwrap_or("input.txt");
    println!("The file passed is: {}", myfile);

    let num_str = matches.value_of("num");
    match num_str {
        None => println!("No idea what your favorite number is."),
        Some(s) => {
            match s.parse::<i32>() {
                Ok(n) => println!("Your favorite number must be {}. ", n
+ 5),
                Err(_) => println!("That's not a number! {}", s),
            }
        }
    }
}

```

Usage information is generated by `clap`. The usage for the example application looks like this.

```
My Test Program 0.1.0
Hackerman Jones <hckrmnjones@hack.gov>
Teaches argument parsing
```

USAGE:

```
testing [OPTIONS]
```

FLAGS:

```
-h, --help          Prints help information
-V, --version       Prints version information
```

OPTIONS:

```
-f, --file <file>    A cool file
-n, --number <num>   Five less than your favorite number
```

We can test the application by running a command like the following.

```
$ cargo run -- -f myfile.txt -n 251
```

The output is:

```
The file passed is: myfile.txt
Your favorite number must be 256.
```

ANSI Terminal

ANSI Terminal

`ansi_term v0.11.0` Command line

This program depicts the use of `ansi_term crate` and how it is used for controlling colours and formatting, such as blue bold text or yellow underlined text, on ANSI terminals.

There are two main data structures in `[ansi_term]`: `ANSIString` and `Style`. A `Style` holds stylistic information: colours, whether the text should be bold, or blinking, or whatever. There are also `Colour` variants that represent simple foreground colour styles. An `ANSIString` is a string paired with a `Style`.

Note: British English uses *Colour* instead of *Color*, don't get confused

Printing colored text to the Terminal

```
extern crate ansi_term;

use ansi_term::Colour;

fn main() {
    println!("This is {} in color, {} in color and {} in color",
            Colour::Red.paint("red"),
            Colour::Blue.paint("blue"),
            Colour::Green.paint("green"));
}
```

Bold text in Terminal

For anything more complex than plain foreground colour changes, the code needs to construct `style` struct. `Style::new()` creates the struct, and properties chained.

```
extern crate ansi_term;

use ansi_term::Style;

fn main() {
    println!("{}", and this is not",
            Style::new().bold().paint("This is Bold"));
}
```

Bold and colored text in terminal

`colour` implements many similar functions as `style` and can chain methods.

```
extern crate ansi_term;

use ansi_term::Colour;
use ansi_term::Style;

fn main(){
    println!("{}", {}, {} and {}",
            Colour::Yellow.paint("This is colored"),
            Style::new().bold().paint("this is bold"),
            Colour::Yellow.bold().paint("this is bold and colored"));
}
```

Compression

| Recipe | Crates | Categories |
|---|-------------------------------|-------------|
| Decompress a tarball | flate2 v1.0.13 tar v0.4.26 | Compression |
| Compress a directory into a tarball | flate2 v1.0.13 tar v0.4.26 | Compression |
| Decompress a tarball while removing a prefix from the paths | flate2 v1.0.13 tar v0.4.26 | Compression |

Working with Tarballs

Decompress a tarball

flate2 v1.0.13 tar v0.4.26 Compression

Decompress (`GzDecoder`) and extract (`Archive::unpack`) all files from a compressed tarball named `archive.tar.gz` located in the current working directory to the same location.

```
extern crate flate2;
extern crate tar;

use std::fs::File;
use flate2::read::GzDecoder;
use tar::Archive;

fn main() -> Result<(), std::io::Error> {
    let path = "archive.tar.gz";

    let tar_gz = File::open(path)?;
    let tar = GzDecoder::new(tar_gz);
    let mut archive = Archive::new(tar);
    archive.unpack(".")?;

    Ok(())
}
```

Compress a directory into tarball

flate2 v1.0.13 tar v0.4.26 Compression

Compress `/var/log` directory into `archive.tar.gz`.

Creates a `File` wrapped in `GzEncoder` and `tar::Builder`.

Adds contents of `/var/log` directory recursively into the archive under `backup/logs` path with `Builder::append_dir_all`. `GzEncoder` is responsible for transparently compressing the data prior to writing it into `archive.tar.gz`.

```
extern crate tar;
extern crate flate2;

use std::fs::File;
use flate2::Compression;
use flate2::write::GzEncoder;

fn main() -> Result<(), std::io::Error> {
    let tar_gz = File::create("archive.tar.gz");
    let enc = GzEncoder::new(tar_gz, Compression::default());
    let mut tar = tar::Builder::new(enc);
    tar.append_dir_all("backup/logs", "/var/log");
    Ok(())
}
```

Decompress a tarball while removing a prefix from the paths

flate2 v1.0.13 tar v0.4.26 Compression

Iterate over the `Archive::entries`. Use `Path::strip_prefix` to remove the specified path prefix (`bundle/logs`). Finally, extract the `tar::Entry` via `Entry::unpack`.

```

extern crate flate2;
extern crate tar;

use std::fs::File;
use std::path::PathBuf;
use flate2::read::GzDecoder;
use tar::Archive;

fn main() -> Result<()> {
    let file = File::open("archive.tar.gz")?;
    let mut archive = Archive::new(GzDecoder::new(file));
    let prefix = "bundle/logs";

    println!("Extracted the following files:");
    archive
        .entries()?
        .filter_map(|e| e.ok())
        .map(|mut entry| -> Result<PathBuf> {
            let path = entry.path()?.strip_prefix(prefix)?.to_owned();
            entry.unpack(&path)?;
            Ok(path)
        })
        .filter_map(|e| e.ok())
        .for_each(|x| println!("> {}", x.display()));

    Ok(())
}

```

Concurrency

| Recipe | Crates | Categories |
|--|-------------------------|---------------|
| Spawn a short-lived thread | crossbeam v0.7.3 | Concurrency |
| Pass data between two threads | crossbeam v0.7.3 | Concurrency |
| Maintain global mutable state | lazy_static v1.4.0 | Rust patterns |
| Calculate SHA1 sum of *.iso files concurrently | threadpool v1.7.1 | Concurrency |
| | walkdir v2.3.1 | |
| | num_cpus v1.12.0 | Filesystem |
| | ring v0.16.10 | |
| Draw fractal dispatching work to a thread pool | threadpool v1.7.1 | Concurrency |
| | num v0.2.1 | Science |
| | num_cpus v1.12.0 | Rendering |
| | image v0.23.0-preview.0 | |

| Recipe | Crates | Categories |
|---|--|---------------------------|
| Mutate the elements of an array in parallel | rayon v1.3.0 | Concurrency |
| Test in parallel if any or all elements of a collection match a given predicate | rayon v1.3.0 | Concurrency |
| Search items using given predicate in parallel | rayon v1.3.0 | Concurrency |
| Sort a vector in parallel | rayon v1.3.0 rand v0.7.3 | Concurrency |
| Map-reduce in parallel | rayon v1.3.0 | Concurrency |
| Generate jpg thumbnails in parallel | rayon v1.3.0 glob v0.3.0 image v0.23.0-preview.0 | Concurrency Filesystem |

Threads

Spawn a short-lived thread

crossbeam v0.7.3 Concurrency

The example uses the `crossbeam` crate, which provides data structures and functions for concurrent and parallel programming. `Scope::spawn` spawns a new scoped thread that is guaranteed to terminate before returning from the closure that passed into `crossbeam::scope` function, meaning that you can reference data from the calling function.

This example splits the array in half and performs the work in separate threads.

```
extern crate crossbeam;

fn main() {
    let arr = &[1, 25, -4, 10];
    let max = find_max(arr);
    assert_eq!(max, Some(25));
}

fn find_max(arr: &[i32]) -> Option<i32> {
    const THRESHOLD: usize = 2;

    if arr.len() <= THRESHOLD {
        return arr.iter().cloned().max();
    }

    let mid = arr.len() / 2;
    let (left, right) = arr.split_at(mid);

    crossbeam::scope(|s| {
        let thread_l = s.spawn(|_| find_max(left));
        let thread_r = s.spawn(|_| find_max(right));

        let max_l = thread_l.join().unwrap()?;
        let max_r = thread_r.join().unwrap()?;

        Some(max_l.max(max_r))
    }).unwrap()
}
```

Pass data between two threads

crossbeam v0.7.3 Concurrency

This example demonstrates the use of [crossbeam-channel](#) in a single producer, single consumer (SPSC) setting. We build off the [ex-crossbeam-spawn](#) example by using [crossbeam::scope](#) and [Scope::spawn](#) to manage the producer thread. Data is exchanged between the two threads using a [crossbeam_channel::unbounded](#) channel, meaning there is no limit to the number of storeable messages. The producer thread sleeps for half a second in between messages.

```
extern crate crossbeam;
extern crate crossbeam_channel;

use std::{thread, time};
use crossbeam_channel::unbounded;

fn main() {
    let (snd, rcv) = unbounded();
    let n_msgs = 5;
    crossbeam::scope(|s| {
        s.spawn(|_| {
            for i in 0..n_msgs {
                snd.send(i).unwrap();
                thread::sleep(time::Duration::from_millis(100));
            }
        });
    }).unwrap();
    for _ in 0..n_msgs {
        let msg = rcv.recv().unwrap();
        println!("Received {}", msg);
    }
}
```

Maintain global mutable state

lazy_static v1.4.0 Rust patterns

Declare global state using [lazy_static](#). [lazy_static](#) creates a globally available `static ref` which requires a [Mutex](#) to allow mutation (also see [RwLock](#)). The [Mutex](#) wrap ensures the state cannot be simultaneously accessed by multiple threads, preventing race conditions. A [MutexGuard](#) must be acquired to read or mutate the value stored in a [Mutex](#).

```
#[macro_use]
extern crate lazy_static;

use std::sync::Mutex;

lazy_static! {
    static ref FRUIT: Mutex<Vec<String>> = Mutex::new(Vec::new());
}

fn insert(fruit: &str) -> Result<()> {
    let mut db = FRUIT.lock().map_err(|_| "Failed to acquire
MutexGuard")?;
    db.push(fruit.to_string());
    Ok(())
}

fn main() -> Result<()> {
    insert("apple")?;
    insert("orange")?;
    insert("peach")?;
    {
        let db = FRUIT.lock().map_err(|_| "Failed to acquire
MutexGuard")?;

        db.iter().enumerate().for_each(|(i, item)| println!("{}", i,
item));
    }
    insert("grape")?;
    Ok(())
}
```

Calculate SHA1 sum of iso files concurrently

threadpool v1.7.1 num_cpus v1.12.0 walkdir v2.3.1 ring v0.16.10 Concurrency Filesystem

This example calculates the SHA1 for every file with iso extension in the current directory. A threadpool generates threads equal to the number of cores present in the system found with `num_cpus::get`. `Walkdir::new` iterates the current directory and calls `execute` to perform the operations of reading and computing SHA1 hash.

```
extern crate walkdir;
extern crate ring;
extern crate num_cpus;
extern crate threadpool;

use walkdir::WalkDir;
use std::fs::File;
use std::io::{BufReader, Read, Error};
use std::path::Path;
use threadpool::ThreadPool;
use std::sync::mpsc::channel;
use ring::digest::{Context, Digest, SHA1};

fn compute_digest<P: AsRef<Path>>(filepath: P) -> Result<(Digest, P),
Error> {
    let mut buf_reader = BufReader::new(File::open(&filepath)?);
    let mut context = Context::new(&SHA1);
    let mut buffer = [0; 1024];

    loop {
        let count = buf_reader.read(&mut buffer)?;
        if count == 0 {
            break;
        }
        context.update(&buffer[..count]);
    }

    Ok((context.finish(), filepath))
}

fn main() -> Result<(), Error> {
    let pool = ThreadPool::new(num_cpus::get());

    let (tx, rx) = channel();

    for entry in WalkDir::new("/home/user/Downloads")
        .follow_links(true)
        .into_iter()
        .filter_map(|e| e.ok())
        .filter(|e| !e.path().is_dir() && is_iso(e.path())) {
        let path = entry.path().to_owned();
        let tx = tx.clone();
        pool.execute(move || {
            let digest = compute_digest(path);
            tx.send(digest).expect("Could not send data!");
        });
    }


    drop(tx);
}
```

```
for t in rx.iter() {
    let (sha, path) = t?;
    println!("{:?} {:?}", sha, path);
}
Ok(())
}
```

Draw fractal dispatching work to a thread pool

threadpool v1.7.1 num v0.2.1 num_cpus v1.12.0 image v0.23.0-preview.0 Concurrency Science
Rendering

This example generates an image by drawing a fractal from the [Julia set](#) with a thread pool for distributed computation.



Allocate memory for output image of given width and height with `ImageBuffer::new`. `Rgb::from_channels` calculates RGB pixel values. Create `ThreadPool` with thread count equal to number of cores with `num_cpus::get`. `ThreadPool::execute` receives each pixel as a separate job.

`mpsc::channel` receives the jobs and `Receiver::recv` retrieves them. `ImageBuffer::put_pixel` uses the data to set the pixel color. `ImageBuffer::save` writes the image to `output.png`.

```

extern crate threadpool;
extern crate num;
extern crate num_cpus;
extern crate image;

use std::sync::mpsc::{channel, RecvError};
use threadpool::ThreadPool;
use num::complex::Complex;
use image::{ImageBuffer, Pixel, Rgb};

fn main() -> Result<()> {
    let (width, height) = (1920, 1080);
    let mut img = ImageBuffer::new(width, height);
    let iterations = 300;

    let c = Complex::new(-0.8, 0.156);

    let pool = ThreadPool::new(num_cpus::get());
    let (tx, rx) = channel();

    for y in 0..height {
        let tx = tx.clone();
        pool.execute(move || for x in 0..width {
            let i = julia(c, x, y, width, height,
iterations);
            let pixel = wavelength_to_rgb(380 + i * 400 /
iterations);
            tx.send((x, y, pixel)).expect("Could not send
data!");
        });
    }

    for _ in 0..(width * height) {
        let (x, y, pixel) = rx.recv()?;
        img.put_pixel(x, y, pixel);
    }
    let _ = img.save("output.png");
    Ok(())
}

```

Parallel Tasks

Mutate the elements of an array in parallel

`rayon v1.3.0` `Concurrency`

The example uses the `rayon` crate, which is a data parallelism library for Rust. `rayon` provides the `par_iter_mut` method for any parallel iterable data type. This is an iterator-like chain that potentially executes in parallel.

```
extern crate rayon;

use rayon::prelude::*;

fn main() {
    let mut arr = [0, 7, 9, 11];
    arr.par_iter_mut().for_each(|p| *p -= 1);
    println!("{:?}", arr);
}
```

Test in parallel if any or all elements of a collection match a given predicate

`rayon v1.3.0` `Concurrency`

This example demonstrates using the `rayon::any` and `rayon::all` methods, which are parallelized counterparts to `std::any` and `std::all`. `rayon::any` checks in parallel whether any element of the iterator matches the predicate, and returns as soon as one is found. `rayon::all` checks in parallel whether all elements of the iterator match the predicate, and returns as soon as a non-matching element is found.

```
extern crate rayon;

use rayon::prelude::*;

fn main() {
    let mut vec = vec![2, 4, 6, 8];

    assert!(vec.par_iter().any(|n| (*n % 2) != 0));
    assert!(vec.par_iter().all(|n| (*n % 2) == 0));
    assert!(vec.par_iter().any(|n| *n > 8 ));
    assert!(vec.par_iter().all(|n| *n <= 8 ));

    vec.push(9);

    assert!(vec.par_iter().any(|n| (*n % 2) != 0));
    assert!(vec.par_iter().all(|n| (*n % 2) == 0));
    assert!(vec.par_iter().any(|n| *n > 8 ));
    assert!(vec.par_iter().all(|n| *n <= 8 ));
}
```

Search items using given predicate in parallel

rayon v1.3.0 Concurrency

This example uses `rayon::find_any` and `par_iter` to search a vector in parallel for an element satisfying the predicate in the given closure.

If there are multiple elements satisfying the predicate defined in the closure argument of `rayon::find_any`, `rayon` returns the first one found, not necessarily the first one.

Also note that the argument to the closure is a reference to a reference (`&&x`). See the discussion on `std::find` for additional details.

```
extern crate rayon;

use rayon::prelude::*;

fn main() {
    let v = vec![6, 2, 1, 9, 3, 8, 11];

    let f1 = v.par_iter().find_any(|&&x| x == 9);
    let f2 = v.par_iter().find_any(|&&x| x % 2 == 0 && x > 6);
    let f3 = v.par_iter().find_any(|&&x| x > 8);

    assert_eq!(f1, Some(&9));
    assert_eq!(f2, Some(&8));
    assert!(f3 > Some(&8));
}
```

Sort a vector in parallel

rayon v1.3.0 rand v0.7.3 Concurrency

This example will sort in parallel a vector of Strings.

Allocate a vector of empty Strings. `par_iter_mut().for_each` populates random values in parallel. Although [multiple options](#) exist to sort an enumerable data type, [par_sort_unstable](#) is usually faster than [stable sorting](#) algorithms.

```
extern crate rand;
extern crate rayon;

use rand::{Rng, thread_rng};
use rand::distributions::Alphanumeric;
use rayon::prelude::*;

fn main() {
    let mut vec = vec![String::new(); 100_000];
    vec.par_iter_mut().for_each(|p| {
        let mut rng = thread_rng();
        *p = (0..5).map(|_| rng.sample(&Alphanumeric)).collect()
    });
    vec.par_sort_unstable();
}
```

Map-reduce in parallel

rayon v1.3.0 Concurrency

This example uses `rayon::filter`, `rayon::map`, and `rayon::reduce` to calculate the average age of `Person` objects whose age is over 30.

`rayon::filter` returns elements from a collection that satisfy the given predicate. `rayon::map` performs an operation on every element, creating a new iteration, and `rayon::reduce` performs an operation given the previous reduction and the current element. Also shows use of `rayon::sum`, which has the same result as the reduce operation in this example.

```
extern crate rayon;

use rayon::prelude::*;

struct Person {
    age: u32,
}

fn main() {
    let v: Vec<Person> = vec![
        Person { age: 23 },
        Person { age: 19 },
        Person { age: 42 },
        Person { age: 17 },
        Person { age: 17 },
        Person { age: 31 },
        Person { age: 30 },
    ];

    let num_over_30 = v.par_iter().filter(|&x| x.age > 30).count() as
f32;
    let sum_over_30 = v.par_iter()
        .map(|x| x.age)
        .filter(|&x| x > 30)
        .reduce(|| 0, |x, y| x + y);

    let alt_sum_30: u32 = v.par_iter()
        .map(|x| x.age)
        .filter(|&x| x > 30)
        .sum();

    let avg_over_30 = sum_over_30 as f32 / num_over_30;
    let alt_avg_over_30 = alt_sum_30 as f32 / num_over_30;

    assert!((avg_over_30 - alt_avg_over_30).abs() < std::f32::EPSILON);
    println!("The average age of people older than 30 is {}",
avg_over_30);
}
```

Generate jpg thumbnails in parallel

rayon v1.3.0 glob v0.3.0 image v0.23.0-preview.0 Concurrency Filesystem

This example generates thumbnails for all .jpg files in the current directory then saves them in a new folder called `thumbnails`.

`glob::glob_with` finds jpeg files in current directory. `rayon` resizes images in parallel using `par_iter` calling `DynamicImage::resize`.

```

extern crate glob;
extern crate image;
extern crate rayon;

use std::path::Path;
use std::fs::create_dir_all;

use glob::{glob_with, MatchOptions};
use image::{FilterType, ImageError};
use rayon::prelude::*;

fn main() -> Result<()> {
    let options: MatchOptions = Default::default();
    let files: Vec<_> = glob_with("*.jpg", &options)?
        .filter_map(|x| x.ok())
        .collect();

    if files.len() == 0 {
        bail!("No .jpg files found in current directory");
    }

    let thumb_dir = "thumbnails";
    create_dir_all(thumb_dir)?;

    println!("Saving {} thumbnails into '{}...' ", files.len(),
thumb_dir);

    let image_failures: Vec<_> = files
        .par_iter()
        .map(|path| {
            make_thumbnail(path, thumb_dir, 300)
                .map_err(|e| e.chain_err(|| path.display().to_string()))
        })
        .filter_map(|x| x.err())
        .collect();

    image_failures.iter().for_each(|x| println!("{}",
x.display_chain()));

    println!("{}", thumbnails saved successfully", files.len() -
image_failures.len());
    Ok(())
}

fn make_thumbnail<PA, PB>(original: PA, thumb_dir: PB, longest_edge:
u32) -> Result<()>
where
    PA: AsRef<Path>,
    PB: AsRef<Path>,

```

```

{
  let img = image::open(original.as_ref())?;
  let file_path = thumb_dir.as_ref().join(original);

  Ok(img.resize(longest_edge, longest_edge, FilterType::Nearest)
    .save(file_path)?)
}

```

Cryptography

| Recipe | Crates | Categories |
|---|---------------------------------------|--------------|
| Calculate the SHA-256 digest of a file | ring v0.16.10 data-encoding v2.1.2 | Cryptography |
| Sign and verify a message with an HMAC digest | ring v0.16.10 | Cryptography |
| Salt and hash a password with PBKDF2 | ring v0.16.10 data-encoding v2.1.2 | Cryptography |

Hashing

Calculate the SHA-256 digest of a file

ring v0.16.10 data-encoding v2.1.2 Cryptography

Writes some data to a file, then calculates the SHA-256 `digest::Digest` of the file's contents using `digest::Context`.

```
extern crate data_encoding;
extern crate ring;

use data_encoding::HEXUPPER;
use ring::digest::{Context, Digest, SHA256};
use std::fs::File;
use std::io::{BufReader, Read, Write};

fn sha256_digest<R: Read>(mut reader: R) -> Result<Digest> {
    let mut context = Context::new(&SHA256);
    let mut buffer = [0; 1024];

    loop {
        let count = reader.read(&mut buffer)?;
        if count == 0 {
            break;
        }
        context.update(&buffer[..count]);
    }

    Ok(context.finish())
}

fn main() -> Result<()> {
    let path = "file.txt";

    let mut output = File::create(path)?;
    write!(output, "We will generate a digest of this text");

    let input = File::open(path)?;
    let reader = BufReader::new(input);
    let digest = sha256_digest(reader)?;

    println!("SHA-256 digest is {}", HEXUPPER.encode(digest.as_ref()));

    Ok(())
}
```

Sign and verify a message with HMAC digest

ring v0.16.10 Cryptography

Uses `ring::hmac` to creates a `hmac::Signature` of a string then verifies the signature is correct.

```
extern crate ring;

use ring::{digest, hmac, rand};
use ring::rand::SecureRandom;
use ring::error::Unspecified;

fn main() -> Result<(), Unspecified> {
    let mut key_value = [0u8; 48];
    let rng = rand::SystemRandom::new();
    rng.fill(&mut key_value)?;
    let key = hmac::SigningKey::new(&digest::SHA256, &key_value);

    let message = "Legitimate and important message.";
    let signature = hmac::sign(&key, message.as_bytes());
    hmac::verify_with_own_key(&key, message.as_bytes(),
signature.as_ref())?;

    Ok(())
}
```

Encryption

Salt and hash a password with PBKDF2

ring v0.16.10 data-encoding v2.1.2 Cryptography

Uses `ring::pbkdf2` to hash a salted password using the PBKDF2 key derivation function `pbkdf2::derive`. Verifies the hash is correct with `pbkdf2::verify`. The salt is generated using `SecureRandom::fill`, which fills the salt byte array with securely generated random numbers.

```
extern crate ring;
extern crate data_encoding;

use data_encoding::HEXUPPER;
use ring::error::Unspecified;
use ring::rand::SecureRandom;
use ring::{digest, pbkdf2, rand};
use std::num::NonZeroU32;

fn main() -> Result<(), Unspecified> {
    const CREDENTIAL_LEN: usize = digest::SHA512_OUTPUT_LEN;
    let n_iter = NonZeroU32::new(100_000).unwrap();
    let rng = rand::SystemRandom::new();

    let mut salt = [0u8; CREDENTIAL_LEN];
    rng.fill(&mut salt)?;

    let password = "Guess Me If You Can!";
    let mut pbkdf2_hash = [0u8; CREDENTIAL_LEN];
    pbkdf2::derive(
        pbkdf2::PBKDF2_HMAC_SHA512,
        n_iter,
        &salt,
        password.as_bytes(),
        &mut pbkdf2_hash,
    );
    println!("Salt: {}", HEXUPPER.encode(&salt));
    println!("PBKDF2 hash: {}", HEXUPPER.encode(&pbkdf2_hash));

    let should_succeed = pbkdf2::verify(
        pbkdf2::PBKDF2_HMAC_SHA512,
        n_iter,
        &salt,
        password.as_bytes(),
        &pbkdf2_hash,
    );
    let wrong_password = "Definitely not the correct password";
    let should_fail = pbkdf2::verify(
        pbkdf2::PBKDF2_HMAC_SHA512,
        n_iter,
        &salt,
        wrong_password.as_bytes(),
        &pbkdf2_hash,
    );

    assert!(should_succeed.is_ok());
    assert!(!should_fail.is_ok());

    Ok(())
}
```

Data Structures

| Recipe | Crates | Categories |
|--|-----------------|------------|
| Define and operate on a type represented as a bitfield | bitflags v1.2.1 | No std |

Custom

Define and operate on a type represented as a bitfield

bitflags v1.2.1 No std

Creates type safe bitfield type `MyFlags` with help of `bitflags!` macro and implements elementary `clear` operation as well as `Display` trait for it. Subsequently, shows basic bitwise operations and formatting.

| Recipe | Crates | Categories |
|--|------------------|------------|
| Create a SQLite database | rusqlite v0.21.0 | Database |
| Insert and Query data | rusqlite v0.21.0 | Database |
| Create tables in a Postgres database | postgres v0.17.1 | Database |
| Insert and Query data | postgres v0.17.1 | Database |
| Aggregate data | postgres v0.17.1 | Database |

SQLite

Create a SQLite database

rusqlite v0.21.0 Database

Use the `rusqlite` crate to open SQLite databases. See [crate](#) for compiling on Windows.

`Connection::open` will create the database if it doesn't already exist.

```
extern crate rusqlite;

use rusqlite::{Connection, Result};
use rusqlite::NO_PARAMS;

fn main() -> Result<()> {
    let conn = Connection::open("cats.db")?;

    conn.execute(
        "create table if not exists cat_colors (
            id integer primary key,
            name text not null unique
        )",
        NO_PARAMS,
    )?;
    conn.execute(
        "create table if not exists cats (
            id integer primary key,
            name text not null,
            color_id integer not null references cat_colors(id)
        )",
        NO_PARAMS,
    )?;

    Ok(())
}
```

Insert and Select data

rusqlite v0.21.0 Database

`Connection::open` will open the database `cats` created in the earlier recipe. This recipe inserts data into `cat_colors` and `cats` tables using the `execute` method of `Connection`. First, the data is inserted into the `cat_colors` table. After a record for a color is inserted, `last_insert_rowid` method of `Connection` is used to get `id` of the last color inserted. This `id` is used while inserting data into the `cats` table. Then, the select query is prepared using the `prepare` method which gives a `statement` struct. Then, query is executed using `query_map` method of `statement`.

```
extern crate rusqlite;

use rusqlite::NO_PARAMS;
use rusqlite::{Connection, Result};
use std::collections::HashMap;

#[derive(Debug)]
struct Cat {
    name: String,
    color: String,
}

fn main() -> Result<()> {
    let conn = Connection::open("cats.db")?;

    let mut cat_colors = HashMap::new();
    cat_colors.insert(String::from("Blue"), vec!["Tigger", "Sammy"]);
    cat_colors.insert(String::from("Black"), vec!["Oreo", "Biscuit"]);

    for (color, catnames) in &cat_colors {
        conn.execute(
            "INSERT INTO cat_colors (name) values (?1)",
            [&color.to_string()],
        )?;
        let last_id: String = conn.last_insert_rowid().to_string();

        for cat in catnames {
            conn.execute(
                "INSERT INTO cats (name, color_id) values (?1, ?2)",
                [&cat.to_string(), &last_id],
            )?;
        }
    }
    let mut stmt = conn.prepare(
        "SELECT c.name, cc.name from cats c
        INNER JOIN cat_colors cc
        ON cc.id = c.color_id;",
    )?;

    let cats = stmt.query_map(NO_PARAMS, |row| {
        Ok(Cat {
            name: row.get(0)?,
            color: row.get(1)?,
        })
    })?;

    for cat in cats {
        println!("Found cat {:?}", cat);
    }
}
```

```
    Ok(())  
}
```

Using transactions

rusqlite v0.21.0 Database

`Connection::open` will open the `cats.db` database from the top recipe.

Begin a transaction with `Connection::transaction`. Transactions will roll back unless committed explicitly with `Transaction::commit`.

In the following example, colors are added to a table having a unique constraint on the color name. When an attempt to insert a duplicate color is made, the transaction rolls back.

```
extern crate rusqlite;

use rusqlite::{Connection, Result, NO_PARAMS};

fn main() -> Result<()> {
    let mut conn = Connection::open("cats.db")?;

    successful_tx(&mut conn)?;

    let res = rolled_back_tx(&mut conn);
    assert!(res.is_err());

    Ok(())
}

fn successful_tx(conn: &mut Connection) -> Result<()> {
    let tx = conn.transaction()?;

    tx.execute("delete from cat_colors", NO_PARAMS)?;
    tx.execute("insert into cat_colors (name) values (?1)",
    &["lavender"])?;
    tx.execute("insert into cat_colors (name) values (?1)",
    &["blue"])?;

    tx.commit()
}

fn rolled_back_tx(conn: &mut Connection) -> Result<()> {
    let tx = conn.transaction()?;

    tx.execute("delete from cat_colors", NO_PARAMS)?;
    tx.execute("insert into cat_colors (name) values (?1)",
    &["lavender"])?;
    tx.execute("insert into cat_colors (name) values (?1)",
    &["blue"])?;
    tx.execute("insert into cat_colors (name) values (?1)",
    &["lavender"])?;

    tx.commit()
}
```

Working with Postgres

Create tables in a Postgres database

postgres v0.17.1 Database

Use the `postgres` crate to create tables in a Postgres database.

`Connection::connect` helps in connecting to an existing database. The recipe uses a URL string format with `Connection::connect`. It assumes an existing database named `library`, the username is `postgres` and the password is `postgres`.

```
extern crate postgres;

use postgres::{Connection, TlsMode, Error};

fn main() -> Result<(), Error> {
    let conn =
        Connection::connect("postgresql://postgres:postgres@localhost/library",
                            TlsMode::None)?;

    conn.execute("CREATE TABLE IF NOT EXISTS author (
                    id          SERIAL PRIMARY KEY,
                    name        VARCHAR NOT NULL,
                    country     VARCHAR NOT NULL
                )", &[])?;

    conn.execute("CREATE TABLE IF NOT EXISTS book (
                    id          SERIAL PRIMARY KEY,
                    title        VARCHAR NOT NULL,
                    author_id    INTEGER NOT NULL REFERENCES author
                )", &[])?;

    Ok(())
}
```

Insert and Query data

postgres v0.17.1 Database

The recipe inserts data into the `author` table using `execute` method of `Connection`. Then, displays the data from the `author` table using `query` method of `Connection`.

```
extern crate postgres;

use postgres::{Connection, TlsMode, Error};
use std::collections::HashMap;

struct Author {
    id: i32,
    name: String,
    country: String
}

fn main() -> Result<(), Error> {
    let conn =
    Connection::connect("postgresql://postgres:postgres@localhost/library",
                       TlsMode::None)?;

    let mut authors = HashMap::new();
    authors.insert(String::from("Chinua Achebe"), "Nigeria");
    authors.insert(String::from("Rabindranath Tagore"), "India");
    authors.insert(String::from("Anita Nair"), "India");

    for (key, value) in &authors {
        let author = Author {
            id: 0,
            name: key.to_string(),
            country: value.to_string()
        };

        conn.execute("INSERT INTO author (name, country) VALUES ($1,
$2)",
                    &[&author.name, &author.country])?;
    }

    for row in &conn.query("SELECT id, name, country FROM author", &[])?
    {
        let author = Author {
            id: row.get(0),
            name: row.get(1),
            country: row.get(2),
        };
        println!("Author {} is from {}", author.name, author.country);
    }

    Ok(())
}
```

Aggregate data

postgres v0.17.1 Database

This recipe lists the nationalities of the first 7999 artists in the database of the [Museum of Modern Art](#) in descending order.

```
extern crate postgres;
use postgres::{Connection, Error, TlsMode};

struct Nation {
    nationality: String,
    count: i64,
}

fn main() -> Result<(), Error> {
    let conn = Connection::connect(
        "postgres://postgres:postgres@127.0.0.1/moma",
        TlsMode::None,
    )?;

    for row in &conn.query(
        ("SELECT nationality, COUNT(nationality) AS count
        FROM artists GROUP BY nationality ORDER BY count DESC", &[])? {

        let (nationality, count) : (Option<String>, Option<i64>)
        = (row.get (0), row.get (1));

        if nationality.is_some () && count.is_some () {

            let nation = Nation{
                nationality: nationality.unwrap(),
                count: count.unwrap(),
            };
            println!("{}", nation.nationality, nation.count);

        }
    }

    Ok(())
}
```

Date and Time

Recipe

Crates

Categories

| Recipe | Crates | Categories |
|---|----------------|---------------|
| Measure elapsed time | std 1.29.1 | Time |
| Perform checked date and time calculations | chrono v0.4.10 | Date and time |
| Convert a local time to another timezone | chrono v0.4.10 | Date and time |
| Examine the date and time | chrono v0.4.10 | Date and time |
| Convert date to UNIX timestamp and vice versa | chrono v0.4.10 | Date and time |
| Display formatted date and time | chrono v0.4.10 | Date and time |
| Parse string into DateTime struct | chrono v0.4.10 | Date and time |

Duration and Calculation

Measure the elapsed time between two code sections

std 1.29.1 Time

Measures `time::Instant::elapsed` since `time::Instant::now`.

Calling `time::Instant::elapsed` returns a `time::Duration` that we print at the end of the example. This method will not mutate or reset the `time::Instant` object.

```
use std::time::{Duration, Instant};

fn main() {
    let start = Instant::now();
    expensive_function();
    let duration = start.elapsed();

    println!("Time elapsed in expensive_function() is: {:?}", duration);
}
```

Perform checked date and time calculations

chrono v0.4.10 Date and time

Calculates and displays the date and time two weeks from now using `DateTime::checked_add_signed` and the date of the day before that using `DateTime::checked_sub_signed`. The methods return `None` if the date and time cannot be calculated.

Escape sequences that are available for the `DateTime::format` can be found at `chrono::format::strftime`.

```
extern crate chrono;
use chrono::{DateTime, Duration, Utc};

fn day_earlier(date_time: DateTime<Utc>) -> Option<DateTime<Utc>> {
    date_time.checked_sub_signed(Duration::days(1))
}

fn main() {
    let now = Utc::now();
    println!("{}", now);

    let almost_three_weeks_from_now =
now.checked_add_signed(Duration::weeks(2))
    .and_then(|in_2weeks|
in_2weeks.checked_add_signed(Duration::weeks(1)))
    .and_then(day_earlier);

    match almost_three_weeks_from_now {
        Some(x) => println!("{}", x),
        None => eprintln!("Almost three weeks from now overflows!"),
    }

    match now.checked_add_signed(Duration::max_value()) {
        Some(x) => println!("{}", x),
        None => eprintln!("We can't use chrono to tell the time for the
Solar System to complete more than one full orbit around the galactic
center."),
    }
}
```

Convert a local time to another timezone

chrono v0.4.10 Date and time

Gets the local time and displays it using `offset::Local::now` and then converts it to the UTC standard using the `DateTime::from_utc` struct method. A time is then converted using the `offset::FixedOffset` struct and the UTC time is then converted to UTC+8 and UTC-2.

```
extern crate chrono;

use chrono::{DateTime, FixedOffset, Local, Utc};

fn main() {
    let local_time = Local::now();
    let utc_time = DateTime::<Utc>::from_utc(local_time.naive_utc(),
    Utc);
    let china_timezone = FixedOffset::east(8 * 3600);
    let rio_timezone = FixedOffset::west(2 * 3600);
    println!("Local time now is {}", local_time);
    println!("UTC time now is {}", utc_time);
    println!(
        "Time in Hong Kong now is {}",
        utc_time.with_timezone(&china_timezone)
    );
    println!("Time in Rio de Janeiro now is {}",
    utc_time.with_timezone(&rio_timezone));
}
```

Parsing and Displaying

Examine the date and time

chrono v0.4.10 Date and time

Gets the current UTC `DateTime` and its hour/minute/second via `TimeLike` and its year/month/day/weekday via `DateLike`.

```
extern crate chrono;
use chrono::{Datelike, Timelike, Utc};

fn main() {
    let now = Utc::now();

    let (is_pm, hour) = now.hour12();
    println!(
        "The current UTC time is {:02}:{:02}:{:02} {}",
        hour,
        now.minute(),
        now.second(),
        if is_pm { "PM" } else { "AM" }
    );
    println!(
        "And there have been {} seconds since midnight",
        now.num_seconds_from_midnight()
    );

    let (is_common_era, year) = now.year_ce();
    println!(
        "The current UTC date is {}-{:02}-{:02} {:?} ({})",
        year,
        now.month(),
        now.day(),
        now.weekday(),
        if is_common_era { "CE" } else { "BCE" }
    );
    println!(
        "And the Common Era began {} days ago",
        now.num_days_from_ce()
    );
}
```

Convert date to UNIX timestamp and vice versa

chrono v0.4.10 Date and time

Converts a date given by `NaiveDate::from_ymd` and `NaiveTime::from_hms` to UNIX timestamp using `NaiveDateTime::timestamp`. Then it calculates what was the date after one billion seconds since January 1, 1970 0:00:00 UTC, using `NaiveDateTime::from_timestamp`.

```
extern crate chrono;

use chrono::{NaiveDate, NaiveDateTime};

fn main() {
    let date_time: NaiveDateTime = NaiveDate::from_ymd(2017, 11,
12).and_hms(17, 33, 44);
    println!(
        "Number of seconds between 1970-01-01 00:00:00 and {} is {}.",
        date_time, date_time.timestamp());

    let date_time_after_a_billion_seconds =
NaiveDateTime::from_timestamp(1_000_000_000, 0);
    println!(
        "Date after a billion seconds since 1970-01-01 00:00:00 was
{}.",
        date_time_after_a_billion_seconds);
}
```

Display formatted date and time

chrono v0.4.10 Date and time

Gets and displays the current time in UTC using `Utc::now`. Formats the current time in the well-known formats RFC 2822 using `DateTime::to_rfc2822` and RFC 3339 using `DateTime::to_rfc3339`, and in a custom format using `DateTime::format`.

```
extern crate chrono;
use chrono::{DateTime, Utc};

fn main() {
    let now: DateTime<Utc> = Utc::now();

    println!("UTC now is: {}", now);
    println!("UTC now in RFC 2822 is: {}", now.to_rfc2822());
    println!("UTC now in RFC 3339 is: {}", now.to_rfc3339());
    println!("UTC now in a custom format is: {}", now.format("%a %b %e
%T %Y"));
}
```

Parse string into DateTime struct

chrono v0.4.10 Date and time

Parses a `DateTime` struct from strings representing the well-known formats [RFC 2822](#), [RFC 3339](#), and a custom format, using `DateTime::parse_from_rfc2822`, `DateTime::parse_from_rfc3339`, and `DateTime::parse_from_str` respectively.

Escape sequences that are available for the `DateTime::parse_from_str` can be found at `chrono::format::strptime`. Note that the `DateTime::parse_from_str` requires that such a `DateTime` struct must be creatable that it uniquely identifies a date and a time. For parsing dates and times without timezones use `NaiveDate`, `NaiveTime`, and `NaiveDateTime`.

```
extern crate chrono;
use chrono::{DateTime, NaiveDate, NaiveDateTime, NaiveTime};
use chrono::format::ParseError;

fn main() -> Result<(), ParseError> {
    let rfc2822 = DateTime::parse_from_rfc2822("Tue, 1 Jul 2003 10:52:37
+0200")?;
    println!("{}", rfc2822);

    let rfc3339 =
DateTime::parse_from_rfc3339("1996-12-19T16:39:57-08:00")?;
    println!("{}", rfc3339);

    let custom = DateTime::parse_from_str("5.8.1994 8:00 am +0000",
"%d.%m.%Y %H:%M %P %z")?;
    println!("{}", custom);

    let time_only = NaiveTime::parse_from_str("23:56:04", "%H:%M:%S")?;
    println!("{}", time_only);

    let date_only = NaiveDate::parse_from_str("2015-09-05", "%Y-%m-
%d")?;
    println!("{}", date_only);

    let no_timezone = NaiveDateTime::parse_from_str("2015-09-05
23:56:04", "%Y-%m-%d %H:%M:%S")?;
    println!("{}", no_timezone);

    Ok(())
}
```

Development Tools

Debugging

| Recipe | Crates | Categories |
|---|---|------------|
| Log a debug message to the console | log v0.4.8 env_logger v0.7.1 | Debugging |
| Log an error message to the console | log v0.4.8 env_logger v0.7.1 | Debugging |
| Log to stdout instead of stderr | log v0.4.8 env_logger v0.7.1 | Debugging |
| Log messages with a custom logger | log v0.4.8 | Debugging |
| Log to the Unix syslog | log v0.4.8 syslog v5.0.0 | Debugging |
| Enable log levels per module | log v0.4.8 env_logger v0.7.1 | Debugging |
| Use a custom environment variable to set up logging | log v0.4.8 env_logger v0.7.1 | Debugging |
| Include timestamp in log messages | log v0.4.8 env_logger v0.7.1 chrono v0.4.10 | Debugging |
| Log messages to a custom location | log v0.4.8 log4rs v0.10.0 | Debugging |

Versioning

| Recipe | Crates | Categories |
|--------------------------------------|---------------|------------|
| Parse and increment a version string | semver v0.9.0 | Config |
| Parse a complex version string | semver v0.9.0 | Config |

| Recipe | Crates | Categories |
|--|---------------|-----------------------|
| Check if given version is pre-release | semver v0.9.0 | Config |
| Find the latest version satisfying given range | semver v0.9.0 | Config |
| Check external command version for compatibility | semver v0.9.0 | Text processing OS |

Build Time

| Recipe | Crates | Categories |
|--|------------|-------------------|
| Compile and link statically to a bundled C library | cc v1.0.50 | Development tools |
| Compile and link statically to a bundled C++ library | cc v1.0.50 | Development tools |
| Compile a C library while setting custom defines | cc v1.0.50 | Development tools |

Debugging

| Recipe | Crates | Categories |
|---|---------------------------------|------------|
| Log a debug message to the console | log v0.4.8 env_logger v0.7.1 | Debugging |
| Log an error message to the console | log v0.4.8 env_logger v0.7.1 | Debugging |
| Log to stdout instead of stderr | log v0.4.8 env_logger v0.7.1 | Debugging |
| Log messages with a custom logger | log v0.4.8 | Debugging |
| Log to the Unix syslog | log v0.4.8 syslog v5.0.0 | Debugging |
| Enable log levels per module | log v0.4.8 env_logger v0.7.1 | Debugging |
| Use a custom environment variable to set up logging | log v0.4.8 env_logger v0.7.1 | Debugging |

| Recipe | Crates | Categories |
|-----------------------------------|---|------------|
| Include timestamp in log messages | log v0.4.8 env_logger v0.7.1 chrono v0.4.10 | Debugging |
| Log messages to a custom location | log v0.4.8 log4rs v0.10.0 | Debugging |

Log Messages

Log a debug message to the console

log v0.4.8 env_logger v0.7.1 Debugging

The `log` crate provides logging utilities. The `env_logger` crate configures logging via an environment variable. The `debug!` macro works like other `std::fmt` formatted strings.

```
#[macro_use]
extern crate log;
extern crate env_logger;

fn execute_query(query: &str) {
    debug!("Executing query: {}", query);
}

fn main() {
    env_logger::init();

    execute_query("DROP TABLE students");
}
```

No output prints when running this code. By default, the log level is `error`, and any lower levels are dropped.

Set the `RUST_LOG` environment variable to print the message:

```
$ RUST_LOG=debug cargo run
```

Cargo prints debugging information then the following line at the very end of the output:

```
DEBUG:main: Executing query: DROP TABLE students
```

Log an error message to the console

log v0.4.8 env_logger v0.7.1 Debugging

Proper error handling considers exceptions exceptional. Here, an error logs to `stderr` with `log`'s convenience macro `error!`.

```
#[macro_use]
extern crate log;
extern crate env_logger;

fn execute_query(_query: &str) -> Result<(), &'static str> {
    Err("I'm afraid I can't do that")
}

fn main() {
    env_logger::init();

    let response = execute_query("DROP TABLE students");
    if let Err(err) = response {
        error!("Failed to execute query: {}", err);
    }
}
```

Log to stdout instead of stderr

log v0.4.8 env_logger v0.7.1 Debugging

Creates a custom logger configuration using the `Builder::target` to set the target of the log output to `Target::Stdout`.

```
#[macro_use]
extern crate log;
extern crate env_logger;

use env_logger::{Builder, Target};

fn main() {
    Builder::new()
        .target(Target::Stdout)
        .init();

    error!("This error has been printed to Stdout");
}
```

Log messages with a custom logger

log v0.4.8 Debugging

Implements a custom logger `ConsoleLogger` which prints to stdout. In order to use the logging macros, `ConsoleLogger` implements the `log::Log` trait and `log::set_logger` installs it.

```

#[macro_use]
extern crate log;

use log::{Record, Level, Metadata, LevelFilter, SetLoggerError};

static CONSOLE_LOGGER: ConsoleLogger = ConsoleLogger;

struct ConsoleLogger;

impl log::Log for ConsoleLogger {
    fn enabled(&self, metadata: &Metadata) -> bool {
        metadata.level() <= Level::Info
    }

    fn log(&self, record: &Record) {
        if self.enabled(record.metadata()) {
            println!("Rust says: {} - {}", record.level(),
record.args());
        }
    }

    fn flush(&self) {}
}

fn main() -> Result<(), SetLoggerError> {
    log::set_logger(&CONSOLE_LOGGER)?;
    log::set_max_level(LevelFilter::Info);

    info!("hello log");
    warn!("warning");
    error!("oops");
    Ok(())
}

```

Log to the Unix syslog

log v0.4.8 syslog v5.0.0 Debugging

Logs messages to [UNIX syslog](#). Initializes logger backend with `syslog::init`. `syslog::Facility` records the program submitting the log entry's classification, `log::LevelFilter` denotes allowed log verbosity and `option<&str>` holds optional application name.

```
#[macro_use]
extern crate log;
extern crate syslog;

use syslog::{Facility, Error};

fn main() -> Result<(), Error> {
    syslog::init(Facility::LOG_USER,
                 log::LevelFilter::Debug,
                 Some("My app name"))?;
    debug!("this is a debug {}", "message");
    error!("this is an error!");
    Ok(())
}
```

Configure Logging

Enable log levels per module

`log` v0.4.8 `env_logger` v0.7.1 `Debugging`

Creates two modules `foo` and nested `foo::bar` with logging directives controlled separately with `RUST_LOG` environmental variable.

```

#[macro_use]
extern crate log;
extern crate env_logger;

mod foo {
    mod bar {
        pub fn run() {
            warn!("[bar] warn");
            info!("[bar] info");
            debug!("[bar] debug");
        }
    }

    pub fn run() {
        warn!("[foo] warn");
        info!("[foo] info");
        debug!("[foo] debug");
        bar::run();
    }
}

fn main() {
    env_logger::init();
    warn!("[root] warn");
    info!("[root] info");
    debug!("[root] debug");
    foo::run();
}

```

`RUST_LOG` environment variable controls `env_logger` output. Module declarations take comma separated entries formatted like `path::to::module=log_level`. Run the `test` application as follows:

```
RUST_LOG="warn,test::foo=info,test::foo::bar=debug" ./test
```

Sets the default `log::Level` to `warn`, module `foo` and module `foo::bar` to `info` and `debug`.

```

WARN:test: [root] warn
WARN:test::foo: [foo] warn
INFO:test::foo: [foo] info
WARN:test::foo::bar: [bar] warn
INFO:test::foo::bar: [bar] info
DEBUG:test::foo::bar: [bar] debug

```

Use a custom environment variable to set up logging

log v0.4.8 env_logger v0.7.1 Debugging

`Builder` configures logging.

`Builder::parse` parses `MY_APP_LOG` environment variable contents in the form of `RUST_LOG` syntax. Then, `Builder::init` initializes the logger. All these steps are normally done internally by `env_logger::init`.

```
#[macro_use]
extern crate log;
extern crate env_logger;

use std::env;
use env_logger::Builder;

fn main() {
    Builder::new()
        .parse(&env::var("MY_APP_LOG").unwrap_or_default())
        .init();

    info!("informational message");
    warn!("warning message");
    error!("this is an error {}", "message");
}
```

Include timestamp in log messages

log v0.4.8 env_logger v0.7.1 chrono v0.4.10 Debugging

Creates a custom logger configuration with `Builder`. Each log entry calls `Local::now` to get the current `DateTime` in local timezone and uses `DateTime::format` with `strftime::specifiers` to format a timestamp used in the final log.

The example calls `Builder::format` to set a closure which formats each message text with timestamp, `Record::level` and body (`Record::args`).

```

#[macro_use]
extern crate log;
extern crate chrono;
extern crate env_logger;

use std::io::Write;
use chrono::Local;
use env_logger::Builder;
use log::LevelFilter;

fn main() {
    Builder::new()
        .format(|buf, record| {
            writeln!(buf,
                "{} [{}] - {}",
                Local::now().format("%Y-%m-%dT%H:%M:%S"),
                record.level(),
                record.args()
            )
        })
        .filter(None, LevelFilter::Info)
        .init();

    warn!("warn");
    info!("info");
    debug!("debug");
}

```

stderr output will contain

```

2017-05-22T21:57:06 [WARN] - warn
2017-05-22T21:57:06 [INFO] - info

```

Log messages to a custom location

log v0.4.8 log4rs v0.10.0 Debugging

[log4rs](#) configures log output to a custom location. [log4rs](#) can use either an external YAML file or a builder configuration.

Create the log configuration with [log4rs::append::file::FileAppender](#). An appender defines the logging destination. The configuration continues with encoding using a custom pattern from [log4rs::encode::pattern](#). Assigns the configuration to [log4rs::config::Config](#) and sets the default [log::LevelFilter](#)

```
#[macro_use]
extern crate log;
extern crate log4rs;

use log::LevelFilter;
use log4rs::append::file::FileAppender;
use log4rs::encode::pattern::PatternEncoder;
use log4rs::config::{Appender, Config, Root};

fn main() -> Result<()> {
    let logfile = FileAppender::builder()
        .encoder(Box::new(PatternEncoder::new("{l} - {m}\n")))
        .build("log/output.log"?;

    let config = Config::builder()
        .appender(Appender::builder().build("logfile",
Box::new(logfile)))
        .build(Root::builder()
            .appender("logfile")
            .build(LevelFilter::Info))?;

    log4rs::init_config(config)?;

    info!("Hello, world!");

    Ok(())
}
```

Versioning

Parse and increment a version string.

semver v0.9.0 Config

Constructs a `semver::Version` from a string literal using `Version::parse`, then increments it by patch, minor, and major version number one by one.

Note that in accordance with the [Semantic Versioning Specification](#), incrementing the minor version number resets the patch version number to 0 and incrementing the major version number resets both the minor and patch version numbers to 0.

```
extern crate semver;

use semver::{Version, SemVerError};

fn main() -> Result<(), SemVerError> {
    let mut parsed_version = Version::parse("0.2.6")?;

    assert_eq!(
        parsed_version,
        Version {
            major: 0,
            minor: 2,
            patch: 6,
            pre: vec![],
            build: vec![],
        }
    );

    parsed_version.increment_patch();
    assert_eq!(parsed_version.to_string(), "0.2.7");
    println!("New patch release: v{}", parsed_version);

    parsed_version.increment_minor();
    assert_eq!(parsed_version.to_string(), "0.3.0");
    println!("New minor release: v{}", parsed_version);

    parsed_version.increment_major();
    assert_eq!(parsed_version.to_string(), "1.0.0");
    println!("New major release: v{}", parsed_version);

    Ok(())
}
```

Parse a complex version string.

semver v0.9.0 [Config](#)

Constructs a `semver::Version` from a complex version string using `Version::parse`. The string contains pre-release and build metadata as defined in the [Semantic Versioning Specification](#).

Note that, in accordance with the Specification, build metadata is parsed but not considered when comparing versions. In other words, two versions may be equal even if their build strings differ.

```
extern crate semver;

use semver::{Identifier, Version, SemVerError};

fn main() -> Result<(), SemVerError> {
    let version_str = "1.0.49-125+g72ee7853";
    let parsed_version = Version::parse(version_str)?;

    assert_eq!(
        parsed_version,
        Version {
            major: 1,
            minor: 0,
            patch: 49,
            pre: vec![Identifier::Numeric(125)],
            build: vec![],
        }
    );
    assert_eq!(
        parsed_version.build,
        vec![Identifier::AlphaNumeric(String::from("g72ee7853"))]
    );

    let serialized_version = parsed_version.to_string();
    assert_eq!(&serialized_version, version_str);

    Ok(())
}
```

Check if given version is pre-release.

semver v0.9.0 [Config](#)

Given two versions, `is_prerelease` asserts that one is pre-release and the other is not.

```
extern crate semver;

use semver::{Version, SemVerError};

fn main() -> Result<(), SemVerError> {
    let version_1 = Version::parse("1.0.0-alpha"?);
    let version_2 = Version::parse("1.0.0"?);

    assert!(version_1.is_prerelease());
    assert!(!version_2.is_prerelease());

    Ok(())
}
```

Find the latest version satisfying given range

semver v0.9.0 [Config](#)

Given a list of version &strs, finds the latest `semver::Version`.
`semver::VersionReq` filters the list with `VersionReq::matches`. Also demonstrates
semver pre-release preferences.

```
extern crate semver;

use semver::{Version, VersionReq};

fn find_max_matching_version<'a, I>(version_req_str: &str, iterable: I)
-> Result<Option<Version>>
where
    I: IntoIterator<Item = &'a str>,
{
    let vreq = VersionReq::parse(version_req_str)?;

    Ok(
        iterable
            .into_iter()
            .filter_map(|s| Version::parse(s).ok())
            .filter(|s| vreq.matches(s))
            .max(),
    )
}

fn main() -> Result<()> {
    assert_eq!(
        find_max_matching_version("<= 1.0.0", vec!["0.9.0", "1.0.0",
"1.0.1"])?,
        Some(Version::parse("1.0.0")?)
    );

    assert_eq!(
        find_max_matching_version(
            ">1.2.3-alpha.3",
            vec![
                "1.2.3-alpha.3",
                "1.2.3-alpha.4",
                "1.2.3-alpha.10",
                "1.2.3-beta.4",
                "3.4.5-alpha.9",
            ]
        )?,
        Some(Version::parse("1.2.3-beta.4")?)
    );

    Ok(())
}
```

Check external command version for compatibility

semver v0.9.0 Text processing OS

Runs `git --version` using `Command`, then parses the version number into a `semver::Version` using `Version::parse`. `VersionReq::matches` compares `semver::VersionReq` to the parsed version. The command output resembles "git version x.y.z".

```
extern crate semver;

use std::process::Command;
use semver::{Version, VersionReq};

fn main() -> Result<()> {
    let version_constraint = "> 1.12.0";
    let version_test = VersionReq::parse(version_constraint)?;
    let output = Command::new("git").arg("--version").output()?;

    if !output.status.success() {
        bail!("Command executed with failing error code");
    }

    let stdout = String::from_utf8(output.stdout)?;
    let version = stdout.split(" ").last().ok_or_else(|| {
        "Invalid command output"
    })?;
    let parsed_version = Version::parse(version)?;

    if !version_test.matches(&parsed_version) {
        bail!("Command version lower than minimum supported version
(found {}, need {})",
            parsed_version, version_constraint);
    }

    Ok(())
}
```

Build Time Tooling

This section covers "build-time" tooling, or code that is run prior to compiling a crate's source code. Conventionally, build-time code lives in a **build.rs** file and is commonly referred to as a "build script". Common use cases include rust code generation and compilation of bundled C/C++/asm code. See [crates.io's documentation on the matter](https://crates.io/docs) for more information.

Compile and link statically to a bundled C library

cc v1.0.50 Development tools

To accommodate scenarios where additional C, C++, or assembly is required in a project, the `cc` crate offers a simple api for compiling bundled C/C++/asm code into static libraries (`.a`) that can be statically linked to by `rustc`.

The following example has some bundled C code (`src/hello.c`) that will be used from rust. Before compiling rust source code, the "build" file (`build.rs`) specified in `Cargo.toml` runs. Using the `cc` crate, a static library file will be produced (in this case, `libhello.a`, see [compile docs](#)) which can then be used from rust by declaring the external function signatures in an `extern` block.

Since the bundled C is very simple, only a single source file needs to be passed to `cc::Build`. For more complex build requirements, `cc::Build` offers a full suite of builder methods for specifying `include` paths and extra compiler `flags`.

`Cargo.toml`

```
[package]
...
build = "build.rs"

[build-dependencies]
cc = "1"

[dependencies]
error-chain = "0.11"
```

`build.rs`

```
extern crate cc;

fn main() {
    cc::Build::new()
        .file("src/hello.c")
        .compile("hello"); // outputs `libhello.a`
}
```

```
src/hello.c
```

```
#include <stdio.h>

void hello() {
    printf("Hello from C!\n");
}

void greet(const char* name) {
    printf("Hello, %s!\n", name);
}
```

```
src/main.rs
```

```
use std::ffi::CString;
use std::os::raw::c_char;

extern {
    fn hello();
    fn greet(name: *const c_char);
}

fn main() -> Result<()> {
    unsafe { hello() }
    let name = prompt("What's your name? ")?;
    let c_name = CString::new(name)?;
    unsafe { greet(c_name.as_ptr()) }
    Ok(())
}
```

Compile and link statically to a bundled C++ library

cc v1.0.50 Development tools

Linking a bundled C++ library is very similar to linking a bundled C library. The two core differences when compiling and statically linking a bundled C++ library are specifying a C++ compiler via the builder method `cpp(true)` and preventing name mangling by the C++ compiler by adding the `extern "C"` section at the top of our C++ source file.

Cargo.toml

```
[package]
...
build = "build.rs"

[build-dependencies]
cc = "1"
```

build.rs

```
extern crate cc;

fn main() {
    cc::Build::new()
        .cpp(true)
        .file("src/foo.cpp")
        .compile("foo");
}
```

src/foo.cpp

```
extern "C" {
    int multiply(int x, int y);
}

int multiply(int x, int y) {
    return x*y;
}
```

src/main.rs

```
extern {
    fn multiply(x : i32, y : i32) -> i32;
}

fn main(){
    unsafe {
        println!("{}", multiply(5,7));
    }
}
```

Compile a C library while setting custom defines

cc v1.0.50 Development tools

It is simple to build bundled C code with custom defines using `cc::Build::define`. The method takes an `Option` value, so it is possible to create defines such as `#define APP_NAME "foo"` as well as `#define WELCOME` (pass `None` as the value for a value-less define). This example builds a bundled C file with dynamic defines set in `build.rs` and prints **"Welcome to foo - version 1.0.2"** when run. Cargo sets some `environment variables` which may be useful for some custom defines.

Cargo.toml

```
[package]
...
version = "1.0.2"
build = "build.rs"

[build-dependencies]
cc = "1"
```

build.rs

```
extern crate cc;

fn main() {
    cc::Build::new()
        .define("APP_NAME", "\"foo\"")
        .define("VERSION", format!("\"{}\"",
env!("CARGO_PKG_VERSION")).as_str())
        .define("WELCOME", None)
        .file("src/foo.c")
        .compile("foo");
}
```

src/foo.c

```
#include <stdio.h>

void print_app_info() {
#ifdef WELCOME
    printf("Welcome to ");
#endif
    printf("%s - version %s\n", APP_NAME, VERSION);
}
```

src/main.rs

```
extern {
    fn print_app_info();
}

fn main(){
    unsafe {
        print_app_info();
    }
}
```

Encoding

| Recipe | Crates | Categories |
|--|------------------------------|------------|
| Percent-encode a string | url v2.1.1 | Encoding |
| Encode a string as application/x-www-form-urlencoded | url v2.1.1 | Encoding |
| Encode and decode hex | data-encoding v2.1.2 | Encoding |
| Encode and decode base64 | base64 v0.11.0 | Encoding |
| Read CSV records | csv v1.1.3 | Encoding |
| Read CSV records with different delimiter | csv v1.1.3 | Encoding |
| Filter CSV records matching a predicate | csv v1.1.3 | Encoding |
| Handle invalid CSV data with Serde | csv v1.1.3 serde v1.0.104 | Encoding |
| Serialize records to CSV | csv v1.1.3 | Encoding |

| Recipe | Crates | Categories |
|---|------------------------------|------------|
| Serialize records to CSV using Serde | csv v1.1.3 serde v1.0.104 | Encoding |
| Transform one column of a CSV file | csv v1.1.3 serde v1.0.104 | Encoding |
| Serialize and deserialize unstructured JSON | serde_json v1.0.45 | Encoding |
| Deserialize a TOML configuration file | toml v0.5.6 | Encoding |
| Read and write integers in little-endian byte order | byteorder v1.3.2 | Encoding |

Character Sets

Percent-encode a string

url v2.1.1 Encoding

Encode an input string with [percent-encoding](#) using the `utf8_percent_encode` function from the `percent-encoding` crate. Then decode using the `percent_decode` function.

```

extern crate percent_encoding;

use percent_encoding::{utf8_percent_encode, percent_decode, AsciiSet,
CONTROLS};
use std::str::Utf8Error;

/// https://url.spec.whatwg.org/#fragment-percent-encode-set
const FRAGMENT: &AsciiSet = &CONTROLS.add(b'
').add(b'\"').add(b'<').add(b'>').add(b'`');

fn main() -> Result<(), Utf8Error> {
    let input = "confident, productive systems programming";

    let iter = utf8_percent_encode(input, FRAGMENT);
    let encoded: String = iter.collect();
    assert_eq!(encoded,
"confident,%20productive%20systems%20programming");

    let iter = percent_decode(encoded.as_bytes());
    let decoded = iter.decode_utf8()?;
    assert_eq!(decoded, "confident, productive systems programming");

    Ok(())
}

```

The encode set defines which bytes (in addition to non-ASCII and controls) need to be percent-encoded. The choice of this set depends on context. For example, `url` encodes `?` in a URL path but not in a query string.

The return value of encoding is an iterator of `&str` slices which collect into a `String`.

Encode a string as application/x-www-form-urlencoded

url v2.1.1 Encoding

Encodes a string into `application/x-www-form-urlencoded` syntax using the `form_urlencoded::byte_serialize` and subsequently decodes it with `form_urlencoded::parse`. Both functions return iterators that collect into a `String`.

```
extern crate url;
use url::form_urlencoded::{byte_serialize, parse};

fn main() {
    let urlencoded: String = byte_serialize("What is
♥?".as_bytes()).collect();
    assert_eq!(urlencoded, "What+is+%E2%9D%A4%3F");
    println!("urlencoded: '{}'", urlencoded);

    let decoded: String = parse(urlencoded.as_bytes())
        .map(|(key, val)| [key, val].concat())
        .collect();
    assert_eq!(decoded, "What is ♥?");
    println!("decoded: '{}'", decoded);
}
```

Encode and decode hex

data-encoding v2.1.2 Encoding

The `data_encoding` crate provides a `HEXUPPER::encode` method which takes a `&[u8]` and returns a `String` containing the hexadecimal representation of the data.

Similarly, a `HEXUPPER::decode` method is provided which takes a `&[u8]` and returns a `Vec<u8>` if the input data is successfully decoded.

The example below converts `&[u8]` data to hexadecimal equivalent. Compares this value to the expected value.

```
extern crate data_encoding;

use data_encoding::{HEXUPPER, DecodeError};

fn main() -> Result<(), DecodeError> {
    let original = b"The quick brown fox jumps over the lazy dog.";
    let expected =
"54686520717569636B2062726F776E20666F78206A756D7073206F76\
 657220746865206C617A7920646F672E";

    let encoded = HEXUPPER.encode(original);
    assert_eq!(encoded, expected);

    let decoded = HEXUPPER.decode(&encoded.into_bytes())?;
    assert_eq!(&decoded[..], &original[..]);

    Ok(())
}
```

Encode and decode base64

base64 v0.11.0 Encoding

Encodes byte slice into `base64` String using `encode` and decodes it with `decode`.

```
extern crate base64;

use std::str;
use base64::{encode, decode};

fn main() -> Result<()> {
    let hello = b"hello rustaceans";
    let encoded = encode(hello);
    let decoded = decode(&encoded)?;

    println!("origin: {}", str::from_utf8(hello)?);
    println!("base64 encoded: {}", encoded);
    println!("back to origin: {}", str::from_utf8(&decoded)?);

    Ok(())
}
```

CSV processing

Read CSV records

csv v1.1.3

Encoding

Reads standard CSV records into `csv::StringRecord` — a weakly typed data representation which expects valid UTF-8 rows. Alternatively, `csv::ByteRecord` makes no assumptions about UTF-8.

```
extern crate csv;
use csv::Error;

fn main() -> Result<(), Error> {
    let csv = "year,make,model,description
1948,Porsche,356,Luxury sports car
1967,Ford,Mustang fastback 1967,American car";

    let mut reader = csv::Reader::from_reader(csv.as_bytes());
    for record in reader.records() {
        let record = record?;
        println!(
            "In {}, {} built the {} model. It is a {}.",
            &record[0],
            &record[1],
            &record[2],
            &record[3]
        );
    }

    Ok(())
}
```

Serde deserializes data into strongly type structures. See the `csv::Reader::deserialize` method.

```
extern crate csv;
#[macro_use]
extern crate serde_derive;

#[derive(Deserialize)]
struct Record {
    year: u16,
    make: String,
    model: String,
    description: String,
}

fn main() -> Result<(), csv::Error> {
    let csv = "year,make,model,description
1948,Porsche,356,Luxury sports car
1967,Ford,Mustang fastback 1967,American car";

    let mut reader = csv::Reader::from_reader(csv.as_bytes());

    for record in reader.deserialize() {
        let record: Record = record?;
        println!(
            "In {}, {} built the {} model. It is a {}.",
            record.year,
            record.make,
            record.model,
            record.description
        );
    }

    Ok(())
}
```

Read CSV records with different delimiter

csv v1.1.3 Encoding

Reads CSV records with a tab `delimiter`.

```
extern crate csv;
use csv::Error;
#[macro_use]
extern crate serde_derive;

#[derive(Debug, Deserialize)]
struct Record {
    name: String,
    place: String,
    #[serde(deserialize_with = "csv::invalid_option")]
    id: Option<u64>,
}

use csv::ReaderBuilder;

fn main() -> Result<(), Error> {
    let data = "name\tplace\tid
Mark\tMelbourne\t46
Ashley\tZurich\t92";

    let mut reader =
ReaderBuilder::new().delimiter(b'\t').from_reader(data.as_bytes());
    for result in reader.deserialize::<Record>() {
        println!("{:?}", result?);
    }

    Ok(())
}
```

Filter CSV records matching a predicate

csv v1.1.3 Encoding

Returns *only* the rows from `data` with a field that matches `query` .

```
extern crate csv;

use std::io;

fn main() -> Result<()> {
    let query = "CA";
    let data = "\
City,State,Population,Latitude,Longitude
Kenai,AK,7610,60.5544444,-151.2583333
Oakman,AL,,33.7133333,-87.3886111
Sandfort,AL,,32.3380556,-85.2233333
West Hollywood,CA,37031,34.0900000,-118.3608333";

    let mut rdr =
csv::ReaderBuilder::new().from_reader(data.as_bytes());
    let mut wtr = csv::Writer::from_writer(io::stdout());

    wtr.write_record(rdr.headers())?;

    for result in rdr.records() {
        let record = result?;
        if record.iter().any(|field| field == query) {
            wtr.write_record(&record)?;
        }
    }

    wtr.flush()?;
    Ok(())
}
```

Disclaimer: this example has been adapted from [the csv crate tutorial](#).

Handle invalid CSV data with Serde

csv v1.1.3 serde v1.0.104 Encoding

CSV files often contain invalid data. For these cases, the `csv` crate provides a custom deserializer, `csv::invalid_option`, which automatically converts invalid data to `None` values.

```
extern crate csv;
use csv::Error;
#[macro_use]
extern crate serde_derive;

#[derive(Debug, Deserialize)]
struct Record {
    name: String,
    place: String,
    #[serde(deserialize_with = "csv::invalid_option")]
    id: Option<u64>,
}

fn main() -> Result<(), Error> {
    let data = "name,place,id
mark,sydney,46.5
ashley,zurich,92
akshat,delhi,37
alisha,colombo,xyz";

    let mut rdr = csv::Reader::from_reader(data.as_bytes());
    for result in rdr.deserialize() {
        let record: Record = result?;
        println!("{:?}", record);
    }

    Ok(())
}
```

Serialize records to CSV

csv v1.1.3 Encoding

This example shows how to serialize a Rust tuple. `csv::writer` supports automatic serialization from Rust types into CSV records. `write_record` writes a simple record containing string data only. Data with more complex values such as numbers, floats, and options use `serialize`. Since CSV writer uses internal buffer, always explicitly `flush` when done.

```
extern crate csv;

use std::io;

fn main() -> Result<()> {
    let mut wtr = csv::Writer::from_writer(io::stdout());

    wtr.write_record(&["Name", "Place", "ID"])?;

    wtr.serialize(("Mark", "Sydney", 87))?;
    wtr.serialize(("Ashley", "Dublin", 32))?;
    wtr.serialize(("Akshat", "Delhi", 11))?;

    wtr.flush()?;
    Ok(())
}
```

Serialize records to CSV using Serde

csv v1.1.3 serde v1.0.104 Encoding

The following example shows how to serialize custom structs as CSV records using the [serde](#) crate.

```
extern crate csv;
#[macro_use]
extern crate serde_derive;

use std::io;

#[derive(Serialize)]
struct Record<'a> {
    name: &'a str,
    place: &'a str,
    id: u64,
}

fn main() -> Result<()> {
    let mut wtr = csv::Writer::from_writer(io::stdout());

    let rec1 = Record { name: "Mark", place: "Melbourne", id: 56};
    let rec2 = Record { name: "Ashley", place: "Sydney", id: 64};
    let rec3 = Record { name: "Akshat", place: "Delhi", id: 98};

    wtr.serialize(rec1)?;
    wtr.serialize(rec2)?;
    wtr.serialize(rec3)?;

    wtr.flush()?;

    Ok(())
}
```

Transform CSV column

csv v1.1.3 serde v1.0.104 Encoding

Transform a CSV file containing a color name and a hex color into one with a color name and an rgb color. Utilizes the [csv](#) crate to read and write the csv file, and [serde](#) to deserialize and serialize the rows to and from bytes.

See [csv::Reader::deserialize](#), [serde::Deserialize](#), and [std::str::FromStr](#)

```

extern crate csv;
#[macro_use]
extern crate serde_derive;
extern crate serde;

use csv::{Reader, Writer};
use serde::{de, Deserialize, Deserializer};
use std::str::FromStr;

#[derive(Debug)]
struct HexColor {
    red: u8,
    green: u8,
    blue: u8,
}

#[derive(Debug, Deserialize)]
struct Row {
    color_name: String,
    color: HexColor,
}

impl FromStr for HexColor {
    type Err = Error;

    fn from_str(hex_color: &str) -> std::result::Result<Self, Self::Err>
    {
        let trimmed = hex_color.trim_matches('#');
        if trimmed.len() != 6 {
            Err("Invalid length of hex string".into())
        } else {
            Ok(HexColor {
                red: u8::from_str_radix(&trimmed[..2], 16)?,
                green: u8::from_str_radix(&trimmed[2..4], 16)?,
                blue: u8::from_str_radix(&trimmed[4..6], 16)?,
            })
        }
    }
}

impl<'de> Deserialize<'de> for HexColor {
    fn deserialize<D>(deserializer: D) -> std::result::Result<Self,
D::Error>
    where
        D: Deserializer<'de>,
    {
        let s = String::deserialize(deserializer)?;
        FromStr::from_str(&s).map_err(de::Error::custom)
    }
}

```

```
fn main() -> Result<()> {
    let data = "color_name,color
red,#ff0000
green,#00ff00
blue,#0000FF
periwinkle,#ccccff
magenta,#ff00ff"
        .to_owned();
    let mut out = Writer::from_writer(vec![]);
    let mut reader = Reader::from_reader(data.as_bytes());
    for result in reader.deserialize::<Row>() {
        let res = result?;
        out.serialize((
            res.color_name,
            res.color.red,
            res.color.green,
            res.color.blue,
        ))?;
    }
    let written = String::from_utf8(out.into_inner()?)?;
    assert_eq!(Some("magenta,255,0,255"), written.lines().last());
    println!("{}", written);
    Ok(())
}
```

Structured Data

Serialize and deserialize unstructured JSON

`serde_json` v1.0.45 `Encoding`

The `serde_json` crate provides a `from_str` function to parse a `&str` of JSON.

Unstructured JSON can be parsed into a universal `serde_json::Value` type that is able to represent any valid JSON data.

The example below shows a `&str` of JSON being parsed. The expected value is declared using the `json!` macro.

```
#[macro_use]
extern crate serde_json;

use serde_json::{Value, Error};

fn main() -> Result<(), Error> {
    let j = r#"{"
        "userid": 103609,
        "verified": true,
        "access_privileges": [
            "user",
            "admin"
        ]
    }"#;

    let parsed: Value = serde_json::from_str(j)?;

    let expected = json!({
        "userid": 103609,
        "verified": true,
        "access_privileges": [
            "user",
            "admin"
        ]
    });

    assert_eq!(parsed, expected);

    Ok(())
}
```

Deserialize a TOML configuration file

toml v0.5.6 Encoding

Parse some TOML into a universal `toml::Value` that is able to represent any valid TOML data.

```
extern crate toml;

use toml::{Value, de::Error};

fn main() -> Result<(), Error> {
    let toml_content = r#"
        [package]
        name = "your_package"
        version = "0.1.0"
        authors = ["You! <you@example.org>"]

        [dependencies]
        serde = "1.0"
    "#;

    let package_info: Value = toml::from_str(toml_content)?;

    assert_eq!(package_info["dependencies"]["serde"].as_str(),
Some("1.0"));
    assert_eq!(package_info["package"]["name"].as_str(),
Some("your_package"));

    Ok(())
}
```

Parse TOML into your own structs using [Serde](#).

```
#[macro_use]
extern crate serde_derive;
extern crate toml;

use toml::de::Error;
use std::collections::HashMap;

#[derive(Deserialize)]
struct Config {
    package: Package,
    dependencies: HashMap<String, String>,
}

#[derive(Deserialize)]
struct Package {
    name: String,
    version: String,
    authors: Vec<String>,
}

fn main() -> Result<(), Error> {
    let toml_content = r#"
        [package]
        name = "your_package"
        version = "0.1.0"
        authors = ["You! <you@example.org>"]

        [dependencies]
        serde = "1.0"
        "#;

    let package_info: Config = toml::from_str(toml_content)?;

    assert_eq!(package_info.package.name, "your_package");
    assert_eq!(package_info.package.version, "0.1.0");
    assert_eq!(package_info.package.authors, vec!["You!
<you@example.org>"]);
    assert_eq!(package_info.dependencies["serde"], "1.0");

    Ok(())
}
```

Read and write integers in little-endian byte order

byteorder v1.3.2 Encoding

`byteorder` can reverse the significant bytes of structured data. This may be necessary when receiving information over the network, such that bytes received are from another system.

```
extern crate byteorder;

use byteorder::{LittleEndian, ReadBytesExt, WriteBytesExt};
use std::io::Error;

#[derive(Default, PartialEq, Debug)]
struct Payload {
    kind: u8,
    value: u16,
}

fn main() -> Result<(), Error> {
    let original_payload = Payload::default();
    let encoded_bytes = encode(&original_payload)?;
    let decoded_payload = decode(&encoded_bytes)?;
    assert_eq!(original_payload, decoded_payload);
    Ok(())
}

fn encode(payload: &Payload) -> Result<Vec<u8>, Error> {
    let mut bytes = vec![];
    bytes.write_u8(payload.kind)?;
    bytes.write_u16::<LittleEndian>(payload.value)?;
    Ok(bytes)
}

fn decode(mut bytes: &[u8]) -> Result<Payload, Error> {
    let payload = Payload {
        kind: bytes.read_u8()?,
        value: bytes.read_u16::<LittleEndian>()?,
    };
    Ok(payload)
}
```

Error Handling

| Recipe | Crates | Categories |
|--|---------------------|---------------|
| Handle errors correctly in main | error-chain v0.12.1 | Rust patterns |
| Avoid discarding errors during error conversions | error-chain v0.12.1 | Rust patterns |

Recipe

Obtain backtrace of complex error scenarios

Crates

error-chain v0.12.1

Categories

Rust patterns

Error Handling

Handle errors correctly in main

error-chain v0.12.1 Rust patterns

Handles error that occur when trying to open a file that does not exist. It is achieved by using [error-chain](#), a library that takes care of a lot of boilerplate code needed in order to [handle errors in Rust](#).

`Io(std::io::Error)` inside [foreign_links](#) allows automatic conversion from `std::io::Error` into `error_chain!` defined type implementing the `Error` trait.

The below recipe will tell how long the system has been running by opening the Unix file `/proc/uptime` and parse the content to get the first number. Returns uptime unless there is an error.

Other recipes in this book will hide the [error-chain](#) boilerplate, and can be seen by expanding the code with the ↗ button.

```
#[macro_use]
extern crate error_chain;

use std::fs::File;
use std::io::Read;

error_chain!{
    foreign_links {
        Io(std::io::Error);
        ParseInt(::std::num::ParseIntError);
    }
}

fn read_uptime() -> Result<u64> {
    let mut uptime = String::new();
    File::open("/proc/uptime)?.read_to_string(&mut uptime)?;

    Ok(uptime
        .split('.')
        .next()
        .ok_or("Cannot parse uptime data")?
        .parse()?)
}

fn main() {
    match read_uptime() {
        Ok(uptime) => println!("uptime: {} seconds", uptime),
        Err(err) => eprintln!("error: {}", err),
    };
}
```

Avoid discarding errors during error conversions

error-chain v0.12.1 Rust patterns

The [error-chain](#) crate makes [matching](#) on different error types returned by a function possible and relatively compact. [ErrorKind](#) determines the error type.

Uses [reqwest](#) to query a random integer generator web service. Converts the string response into an integer. The Rust standard library, [reqwest](#), and the web service can all generate errors. Well defined Rust errors use [foreign_links](#). An additional [ErrorKind](#) variant for the web service error uses `errors` block of the `error_chain!` macro.

```

#[macro_use]
extern crate error_chain;
extern crate reqwest;

use std::io::Read;

error_chain! {
    foreign_links {
        Io(std::io::Error);
        Request(reqwest::Error);
        ParseIntError(std::num::ParseIntError);
    }

    errors { RandomResponseError(t: String) }
}

fn parse_response(mut response: reqwest::Response) -> Result<u32> {
    let mut body = String::new();
    response.read_to_string(&mut body)?;
    body.pop();
    body.parse::<u32>()
        .chain_err(|| ErrorKind::RandomResponseError(body))
}

fn run() -> Result<()> {
    let url =
        format!("https://www.random.org/integers/?num=1&min=0&max=10&
col=1&base=10&format=plain");
    let response = reqwest::get(&url)?;
    let random_value: u32 = parse_response(response)?;

    println!("a random number between 0 and 10: {}", random_value);

    Ok(())
}

fn main() {
    if let Err(error) = run() {
        match *error.kind() {
            ErrorKind::Io(_) => println!("Standard IO error: {:?}",
error),
            ErrorKind::Request(_) => println!("Request error: {:?}",
error),
            ErrorKind::ParseIntError(_) => println!("Standard parse int
error: {:?}", error),
            ErrorKind::RandomResponseError(_) => println!("User defined
error: {:?}", error),
            _ => println!("Other error: {:?}", error),
        }
    }
}

```

```
}
```

Obtain backtrace of complex error scenarios

error-chain v0.12.1 Rust patterns

This recipe shows how to handle a complex error scenario and then print a backtrace. It relies on `chain_err` to extend errors by appending new errors. The error stack can be unwound, thus providing a better context to understand why an error was raised.

The below recipes attempts to deserialize the value `256` into a `u8`. An error will bubble up from Serde then csv and finally up to the user code.

```

#[macro_use]
extern crate error_chain;

#[derive(Debug, Deserialize)]
struct Rgb {
    red: u8,
    blue: u8,
    green: u8,
}

impl Rgb {
    fn from_reader(csv_data: &[u8]) -> Result<Rgb> {
        let color: Rgb = csv::Reader::from_reader(csv_data)
            .deserialize()
            .nth(0)
            .ok_or("Cannot deserialize the first CSV record")?
            .chain_err(|| "Cannot deserialize RGB color")?;

        Ok(color)
    }
}

fn run() -> Result<()> {
    let csv = "red,blue,green
102,256,204";

    let rgb = Rgb::from_reader(csv.as_bytes()).chain_err(|| "Cannot read
CSV data")?;
    println!("{:?} to hexadecimal #{:X}", rgb, rgb);

    Ok(())
}

fn main() {
    if let Err(ref errors) = run() {
        eprintln!("Error level - description");
        errors
            .iter()
            .enumerate()
            .for_each(|(index, error)| eprintln!("L> {} - {}", index,
error));

        if let Some(backtrace) = errors.backtrace() {
            eprintln!("{:?}", backtrace);
        }
    }
}

```

Backtrace error rendered:

Error level - description

↳ 0 - Cannot read CSV data

↳ 1 - Cannot deserialize RGB color

↳ 2 - CSV deserialize error: record 1 (line: 2, byte: 15): field 1: number too large to fit in target type

↳ 3 - field 1: number too large to fit in target type

Run the recipe with `RUST_BACKTRACE=1` to display a detailed `backtrace` associated with this error.

File System

| Recipe | Crates | Categories |
|--|------------------|------------------|
| Read lines of strings from a file | std 1.29.1 | Filesystem |
| Avoid writing and reading from a same file | same_file v1.0.6 | Filesystem |
| Access a file randomly using a memory map | memmap v0.7.0 | Filesystem |
| File names that have been modified in the last 24 hours | std 1.29.1 | Filesystem OS |
| Find loops for a given path | same_file v1.0.6 | Filesystem |
| Recursively find duplicate file names | walkdir v2.3.1 | Filesystem |
| Recursively find all files with given predicate | walkdir v2.3.1 | Filesystem |
| Traverse directories while skipping dotfiles | walkdir v2.3.1 | Filesystem |
| Recursively calculate file sizes at given depth | walkdir v2.3.1 | Filesystem |
| Find all png files recursively | glob v0.3.0 | Filesystem |
| Find all files with given pattern ignoring filename case | glob v0.3.0 | Filesystem |

Read & Write

Read lines of strings from a file

std 1.29.1 Filesystem

Writes a three-line message to a file, then reads it back a line at a time with the `Lines` iterator created by `BufRead::lines`. `File` implements `Read` which provides `BufReader` trait. `File::create` opens a `File` for writing, `File::open` for reading.

```
use std::fs::File;
use std::io::{Write, BufReader, BufRead, Error};

fn main() -> Result<(), Error> {
    let path = "lines.txt";

    let mut output = File::create(path)?;
    write!(output, "Rust\n❤️\nFun")?;

    let input = File::open(path)?;
    let buffered = BufReader::new(input);

    for line in buffered.lines() {
        println!("{}", line?);
    }

    Ok(())
}
```

Avoid writing and reading from a same file

same_file v1.0.6 Filesystem

Use `same_file::Handle` to a file that can be tested for equality with other handles. In this example, the handles of file to be read from and to be written to are tested for equality.

```
extern crate same_file;

use same_file::Handle;
use std::fs::File;
use std::io::{BufRead, BufReader, Error, ErrorKind};
use std::path::Path;

fn main() -> Result<(), Error> {
    let path_to_read = Path::new("new.txt");

    let stdout_handle = Handle::stdout()?;
    let handle = Handle::from_path(path_to_read)?;

    if stdout_handle == handle {
        return Err(Error::new(
            ErrorKind::Other,
            "You are reading and writing to the same file",
        ));
    } else {
        let file = File::open(&path_to_read)?;
        let file = BufReader::new(file);
        for (num, line) in file.lines().enumerate() {
            println!("{}", num, line?.to_uppercase());
        }
    }

    Ok(())
}
```

```
cargo run
```

displays the contents of the file new.txt.

```
cargo run >> ./new.txt
```

errors because the two files are same.

Access a file randomly using a memory map

memmap v0.7.0 Filesystem

Creates a memory map of a file using [memmap](#) and simulates some non-sequential reads from the file. Using a memory map means you just index into a slice rather than dealing with [seek](#) to navigate a File.

The `Mmap::map` function assumes the file behind the memory map is not being modified at the same time by another process or else a [race condition](#) occurs.

```
extern crate memmap;

use memmap::Mmap;
use std::fs::File;
use std::io::{Write, Error};

fn main() -> Result<(), Error> {
    let file = File::open("content.txt"?);
    let map = unsafe { Mmap::map(&file)? };

    let random_indexes = [0, 1, 2, 19, 22, 10, 11, 29];
    assert_eq!(&map[3..13], b"hovercraft");
    let random_bytes: Vec<u8> = random_indexes.iter()
        .map(|&idx| map[idx])
        .collect();
    assert_eq!(&random_bytes[..], b"My loaf!");
    Ok(())
}
```

Directory Traversal

File names that have been modified in the last 24 hours

std 1.29.1 Filesystem

Gets the current working directory by calling `env::current_dir`, then for each entries in `fs::read_dir`, extracts the `DirEntry::path` and gets the metadata via `fs::Metadata`. The `Metadata::modified` returns the `SystemTime::elapsed` time since last modification. `Duration::as_secs` converts the time to seconds and compared with 24 hours (24 * 60 * 60 seconds). `Metadata::is_file` filters out directories.

```

use std::{env, fs};

fn main() -> Result<()> {
    let current_dir = env::current_dir()?;
    println!(
        "Entries modified in the last 24 hours in {:?}:",
        current_dir
    );

    for entry in fs::read_dir(current_dir)? {
        let entry = entry?;
        let path = entry.path();

        let metadata = fs::metadata(&path)?;
        let last_modified = metadata.modified()?.elapsed()?.as_secs();

        if last_modified < 24 * 3600 && metadata.is_file() {
            println!(
                "Last modified: {:?} seconds, is read only: {:?}, size:
{:?} bytes, filename: {:?}",
                last_modified,
                metadata.permissions().readonly(),
                metadata.len(),
                path.file_name().ok_or("No filename")?
            );
        }
    }

    Ok(())
}

```

Find loops for a given path

same_file v1.0.6 Filesystem

Use `same_file::is_same_file` to detect loops for a given path. For example, a loop could be created on a Unix system via symlinks:

```

mkdir -p /tmp/foo/bar/baz
ln -s /tmp/foo/ /tmp/foo/bar/baz/qux

```

The following would assert that a loop exists.

```
extern crate same_file;

use std::io;
use std::path::{Path, PathBuf};
use same_file::is_same_file;

fn contains_loop<P: AsRef<Path>>(path: P) -> io::Result<Option<(PathBuf, PathBuf)>> {
    let path = path.as_ref();
    let mut path_buf = path.to_path_buf();
    while path_buf.pop() {
        if is_same_file(&path_buf, path)? {
            return Ok(Some((path_buf, path.to_path_buf())));
        } else if let Some(looped_paths) = contains_loop(&path_buf)? {
            return Ok(Some(looped_paths));
        }
    }
    return Ok(None);
}

fn main() {
    assert_eq!(
        contains_loop("/tmp/foo/bar/baz/qux/bar/baz").unwrap(),
        Some((
            PathBuf::from("/tmp/foo"),
            PathBuf::from("/tmp/foo/bar/baz/qux")
        ))
    );
}
```

Recursively find duplicate file names

walkdir v2.3.1 Filesystem

Find recursively in the current directory duplicate filenames, printing them only once.

```
extern crate walkdir;

use std::collections::HashMap;
use walkdir::WalkDir;

fn main() {
    let mut filenames = HashMap::new();

    for entry in WalkDir::new(".")
        .into_iter()
        .filter_map(Result::ok)
        .filter(|e| !e.file_type().is_dir()) {
        let f_name = String::from(entry.file_name().to_string_lossy());
        let counter = filenames.entry(f_name.clone()).or_insert(0);
        *counter += 1;

        if *counter == 2 {
            println!("{}", f_name);
        }
    }
}
```

Recursively find all files with given predicate

walkdir v2.3.1 Filesystem

Find JSON files modified within the last day in the current directory. Using `follow_links` ensures symbolic links are followed like they were normal directories and files.

```
extern crate walkdir;

use walkdir::WalkDir;

fn main() -> Result<()> {
    for entry in WalkDir::new(".")
        .follow_links(true)
        .into_iter()
        .filter_map(|e| e.ok()) {
        let f_name = entry.file_name().to_string_lossy();
        let sec = entry.metadata()?.modified()?;

        if f_name.ends_with(".json") && sec.elapsed()?.as_secs() < 86400
        {
            println!("{}", f_name);
        }
    }

    Ok(())
}
```

Traverse directories while skipping dotfiles

walkdir v2.3.1 Filesystem

Uses `filter_entry` to descend recursively into entries passing the `is_not_hidden` predicate thus skipping hidden files and directories. `Iterator::filter` applies to each `WalkDir::DirEntry` even if the parent is a hidden directory.

Root dir `."` yields through `WalkDir::depth` usage in `is_not_hidden` predicate.

```
extern crate walkdir;

use walkdir::{DirEntry, WalkDir};

fn is_not_hidden(entry: &DirEntry) -> bool {
    entry
        .file_name()
        .to_str()
        .map(|s| entry.depth() == 0 || !s.starts_with("."))
        .unwrap_or(false)
}

fn main() {
    WalkDir::new(".")
        .into_iter()
        .filter_entry(|e| is_not_hidden(e))
        .filter_map(|v| v.ok())
        .for_each(|x| println!("{}", x.path().display()));
}
```

Recursively calculate file sizes at given depth

walkdir v2.3.1 Filesystem

Recursion depth can be flexibly set by `WalkDir::min_depth` & `WalkDir::max_depth` methods. Calculates sum of all file sizes to 3 subfolders depth, ignoring files in the root folder.

```
extern crate walkdir;

use walkdir::WalkDir;

fn main() {
    let total_size = WalkDir::new(".")
        .min_depth(1)
        .max_depth(3)
        .into_iter()
        .filter_map(|entry| entry.ok())
        .filter_map(|entry| entry.metadata().ok())
        .filter(|metadata| metadata.is_file())
        .fold(0, |acc, m| acc + m.len());

    println!("Total size: {} bytes.", total_size);
}
```

Find all png files recursively

glob v0.3.0 Filesystem

Recursively find all PNG files in the current directory. In this case, the `**` pattern matches the current directory and all subdirectories.

Use the `**` pattern in any path portion. For example, `/media/**/*.png` matches all PNGs in `media` and its subdirectories.

```
extern crate glob;

use glob::glob;

fn main() -> Result<()> {
    for entry in glob("**/*.png")? {
        println!("{}", entry?.display());
    }

    Ok(())
}
```

Find all files with given pattern ignoring filename case.

glob v0.3.0 Filesystem

Find all image files in the `/media/` directory matching the `img_[0-9]*.png` pattern.

A custom `MatchOptions` struct is passed to the `glob_with` function making the glob pattern case insensitive while keeping the other options `Default`.

```
extern crate glob;

use glob::{glob_with, MatchOptions};

fn main() -> Result<()> {
    let options = MatchOptions {
        case_sensitive: false,
        ..Default::default()
    };

    for entry in glob_with("/media/img_[0-9]*.png", &options)? {
        println!("{}", entry?.display());
    }

    Ok(())
}
```

Hardware Support

| Recipe | Crates | Categories |
|---|------------------|------------------|
| Check number of logical cpu cores | num_cpus v1.12.0 | Hardware support |

Processor

Check number of logical cpu cores

num_cpus v1.12.0 Hardware support

Shows the number of logical CPU cores in current machine using [num_cpus::get].

```
extern crate num_cpus;

fn main() {
    println!("Number of logical cores is {}", num_cpus::get());
}
```

Memory Management

| Recipe | Crates | Categories |
|--------|--------|------------|
|--------|--------|------------|

| Recipe | Crates | Categories |
|-----------------------------------|--------------------|--------------------------|
| Declare lazily evaluated constant | lazy_static v1.4.0 | Caching Rust patterns |

Constants

Declare lazily evaluated constant

lazy_static v1.4.0 Caching Rust patterns

Declares a lazily evaluated constant `HashMap`. The `HashMap` will be evaluated once and stored behind a global static reference.

```
#[macro_use]
extern crate lazy_static;

use std::collections::HashMap;

lazy_static! {
    static ref PRIVILEGES: HashMap<'static str, Vec<'static str>> = {
        let mut map = HashMap::new();
        map.insert("James", vec!["user", "admin"]);
        map.insert("Jim", vec!["user"]);
        map
    };
}

fn show_access(name: &str) {
    let access = PRIVILEGES.get(name);
    println!("{}: {:?}", name, access);
}

fn main() {
    let access = PRIVILEGES.get("James");
    println!("James: {:?}", access);

    show_access("Jim");
}
```

Networking

| Recipe | Crates | Categories |
|--|------------|------------|
| Listen on unused port TCP/IP | std 1.29.1 | Net |

Server

Listen on unused port TCP/IP

std 1.29.1 Net

In this example, the port is displayed on the console, and the program will listen until a request is made. `SocketAddrV4` assigns a random port when setting port to 0.

```
use std::net::{SocketAddrV4, Ipv4Addr, TcpListener};
use std::io::{Read, Error};

fn main() -> Result<(), Error> {
    let loopback = Ipv4Addr::new(127, 0, 0, 1);
    let socket = SocketAddrV4::new(loopback, 0);
    let listener = TcpListener::bind(socket)?;
    let port = listener.local_addr()?;
    println!("Listening on {}, access this port to end the program",
port);
    let (mut tcp_stream, addr) = listener.accept()?; //block until
requested
    println!("Connection received! {:?} is sending data.", addr);
    let mut input = String::new();
    let _ = tcp_stream.read_to_string(&mut input)?;
    println!("{:?} says {}", addr, input);
    Ok(())
}
```

Operating System

| Recipe | Crates | Categories |
|--|--------------|-----------------------|
| Run an external command and process stdout | regex v1.3.4 | OS Text processing |
| Run an external command passing it stdin and check for an error code | regex v1.3.4 | OS Text processing |

| Recipe | Crates | Categories |
|---|------------|-----------------------|
| Run piped external commands | std 1.29.1 | OS |
| Redirect both stdout and stderr of child process to the same file | std 1.29.1 | OS |
| Continuously process child process' outputs | std 1.29.1 | OS Text processing |

External Command

Run an external command and process stdout

regex v1.3.4 OS Text processing

Runs `git log --oneLine` as an external [Command](#) and inspects its [Output](#) using [Regex](#) to get the hash and message of the last 5 commits.

```
extern crate regex;

use std::process::Command;
use regex::Regex;

#[derive(PartialEq, Default, Clone, Debug)]
struct Commit {
    hash: String,
    message: String,
}

fn main() -> Result<()> {
    let output = Command::new("git").arg("log").arg("--
online").output()?;

    if !output.status.success() {
        bail!("Command executed with failing error code");
    }

    let pattern = Regex::new(r"(?x)
        ([0-9a-fA-F]+) # commit hash
        (.*)          # The commit message"?);

    String::from_utf8(output.stdout)?
        .lines()
        .filter_map(|line| pattern.captures(line))
        .map(|cap| {
            Commit {
                hash: cap[1].to_string(),
                message: cap[2].trim().to_string(),
            }
        })
        .take(5)
        .for_each(|x| println!("{:?}", x));

    Ok(())
}
```

Run an external command passing it stdin and check for an error code

std 1.29.1 OS

Opens the `python` interpreter using an external `Command` and passes it a python statement for execution. `Output` of statement is then parsed.

```
use std::collections::HashSet;
use std::io::Write;
use std::process::{Command, Stdio};

fn main() -> Result<()> {
    let mut child = Command::new("python").stdin(Stdio::piped())
        .stderr(Stdio::piped())
        .stdout(Stdio::piped())
        .spawn()?;

    child.stdin
        .as_mut()
        .ok_or("Child process stdin has not been captured!")?
        .write_all(b"import this; copyright(); credits(); exit()");

    let output = child.wait_with_output()?;

    if output.status.success() {
        let raw_output = String::from_utf8(output.stdout)?;
        let words = raw_output.split_whitespace()
            .map(|s| s.to_lowercase())
            .collect::<HashSet<_>>();
        println!("Found {} unique words:", words.len());
        println!("{:#?}", words);
        Ok(())
    } else {
        let err = String::from_utf8(output.stderr)?;
        bail!("External command failed:\n {}", err)
    }
}
```

Run piped external commands

std 1.29.1 OS

Shows up to the 10th biggest files and subdirectories in the current working directory. It is equivalent to running: `du -ah . | sort -hr | head -n 10`.

`Command` s represent a process. Output of a child process is captured with a `Stdio::piped` between parent and child.

```
use std::process::{Command, Stdio};

fn main() -> Result<()> {
    let directory = std::env::current_dir()?;
    let mut du_output_child = Command::new("du")
        .arg("-ah")
        .arg(&directory)
        .stdout(Stdio::piped())
        .spawn()?;

    if let Some(du_output) = du_output_child.stdout.take() {
        let mut sort_output_child = Command::new("sort")
            .arg("-hr")
            .stdin(du_output)
            .stdout(Stdio::piped())
            .spawn()?;

        du_output_child.wait()?;

        if let Some(sort_output) = sort_output_child.stdout.take() {
            let head_output_child = Command::new("head")
                .args(&["-n", "10"])
                .stdin(sort_output)
                .stdout(Stdio::piped())
                .spawn()?;

            let head_stdout = head_output_child.wait_with_output()?;

            sort_output_child.wait()?;

            println!(
                "Top 10 biggest files and directories in '{}':\n{}",
                directory.display(),
                String::from_utf8(head_stdout.stdout).unwrap()
            );
        }
    }

    Ok(())
}
```

Redirect both stdout and stderr of child process to the same file

std 1.29.1 OS

Spawns a child process and redirects `stdout` and `stderr` to the same file. It follows the same idea as [run piped external commands](#), however `process::Stdio` writes to a specified file. `File::try_clone` references the same file handle for `stdout` and `stderr`. It will ensure that both handles write with the same cursor position.

The below recipe is equivalent to run the Unix shell command

```
ls . oops >out.txt 2>&1.
```

```
use std::fs::File;
use std::io::Error;
use std::process::{Command, Stdio};

fn main() -> Result<(), Error> {
    let outputs = File::create("out.txt")?;
    let errors = outputs.try_clone()?;

    Command::new("ls")
        .args(&[".", "oops"])
        .stdout(Stdio::from(outputs))
        .stderr(Stdio::from(errors))
        .spawn()?
        .wait_with_output()?;

    Ok(())
}
```

Continuously process child process' outputs

std 1.29.1 OS

In [Run an external command and process stdout](#), processing doesn't start until external `Command` is finished. The recipe below calls `Stdio::piped` to create a pipe, and reads `stdout` continuously as soon as the `BufReader` is updated.

The below recipe is equivalent to the Unix shell command `journalctl | grep usb`

.

```

use std::process::{Command, Stdio};
use std::io::{BufRead, BufReader, Error, ErrorKind};

fn main() -> Result<(), Error> {
    let stdout = Command::new("journalctl")
        .stdout(Stdio::piped())
        .spawn()?
        .stdout
        .ok_or_else(|| Error::new(ErrorKind::Other, "Could not capture
standard output."))?;

    let reader = BufReader::new(stdout);

    reader
        .lines()
        .filter_map(|line| line.ok())
        .filter(|line| line.find("usb").is_some())
        .for_each(|line| println!("{}", line));

    Ok(())
}

```

Science

Mathematics

| Recipe | Crates | Categories |
|---|------------------|------------|
| Vector Sum | ndarray v0.13.0 | Science |
| Vector Norm | ndarray v0.13.0 | Science |
| Adding matrices | ndarray v0.13.0 | Science |
| Multiplying matrices | ndarray v0.13.0 | Science |
| Multiply a scalar with a vector with a matrix | ndarray v0.13.0 | Science |
| Invert marix | nalgebra v0.19.0 | Science |
| Calculating the side length of a triangle | std 1.29.1 | Science |
| Verifying tan is equal to sin divided by cos | std 1.29.1 | Science |
| Distance between two points on the Earth | std 1.29.1 | Science |
| Creating complex numbers | num v0.2.1 | Science |

| Recipe | Crates | Categories |
|---|------------|------------|
| Adding complex numbers | num v0.2.1 | Science |
| Mathematical functions on complex numbers | num v0.2.1 | Science |
| Measures of central tendency | std 1.29.1 | Science |
| Computing standard deviation | std 1.29.1 | Science |
| Big integers | num v0.2.1 | Science |

Mathematics

| Recipe | Crates | Categories |
|---|------------------|------------|
| Vector Sum | ndarray v0.13.0 | Science |
| Vector Norm | ndarray v0.13.0 | Science |
| Adding matrices | ndarray v0.13.0 | Science |
| Multiplying matrices | ndarray v0.13.0 | Science |
| Multiply a scalar with a vector with a matrix | ndarray v0.13.0 | Science |
| Invert marix | nalgebra v0.19.0 | Science |
| Calculating the side length of a triangle | std 1.29.1 | Science |
| Verifying tan is equal to sin divided by cos | std 1.29.1 | Science |
| Distance between two points on the Earth | std 1.29.1 | Science |
| Creating complex numbers | num v0.2.1 | Science |
| Adding complex numbers | num v0.2.1 | Science |
| Mathematical functions on complex numbers | num v0.2.1 | Science |
| Measures of central tendency | std 1.29.1 | Science |
| Computing standard deviation | std 1.29.1 | Science |
| Big integers | num v0.2.1 | Science |

Linear Algebra

Adding matrices

ndarray v0.13.0 Science

Creates two 2-D matrices with `ndarray::arr2` and sums them element-wise.

Note the sum is computed as `let sum = &a + &b`. The `&` operator is used to avoid consuming `a` and `b`, making them available later for display. A new array is created containing their sum.

```
extern crate ndarray;

use ndarray::arr2;

fn main() {
    let a = arr2(&[[1, 2, 3],
                  [4, 5, 6]]);

    let b = arr2(&[[6, 5, 4],
                  [3, 2, 1]]);

    let sum = &a + &b;

    println!("{}", a);
    println!("+");
    println!("{}", b);
    println!("=");
    println!("{}", sum);
}
```

Multiplying matrices

ndarray v0.13.0 Science

Creates two matrices with `ndarray::arr2` and performs matrix multiplication on them with `ndarray::ArrayBase::dot`.

```
extern crate ndarray;

use ndarray::arr2;

fn main() {
    let a = arr2(&[[1, 2, 3],
                  [4, 5, 6]]);

    let b = arr2(&[[6, 3],
                  [5, 2],
                  [4, 1]]);

    println!("{}", a.dot(&b));
}
```

Multiply a scalar with a vector with a matrix

ndarray v0.13.0 Science

Creates a 1-D array (vector) with `ndarray::arr1` and a 2-D array (matrix) with `ndarray::arr2`.

First, a scalar is multiplied by the vector to get another vector. Then, the matrix is multiplied by the new vector with `ndarray::Array2::dot`. (Matrix multiplication is performed using `dot`, while the `*` operator performs element-wise multiplication.)

In `ndarray`, 1-D arrays can be interpreted as either row or column vectors depending on context. If representing the orientation of a vector is important, a 2-D array with one row or one column must be used instead. In this example, the vector is a 1-D array on the right-hand side, so `dot` handles it as a column vector.

```
extern crate ndarray;

use ndarray::{arr1, arr2, Array1};

fn main() {
    let scalar = 4;

    let vector = arr1(&[1, 2, 3]);

    let matrix = arr2(&[[4, 5, 6],
                        [7, 8, 9]]);

    let new_vector: Array1<_> = scalar * vector;
    println!("{}", new_vector);

    let new_matrix = matrix.dot(&new_vector);
    println!("{}", new_matrix);
}
```

Vector comparison

ndarray v0.13.0

The `ndarray` crate supports a number of ways to create arrays -- this recipe creates `ndarray::Array`s from `std::Vec` using `from`. Then, it sums the arrays element-wise.

This recipe contains an example of comparing two floating-point vectors element-wise. Floating-point numbers are often stored inexactly, making exact comparisons difficult. However, the `assert_abs_diff_eq!` macro from the `approx` crate allows for convenient element-wise comparisons. To use the `approx` crate with `ndarray`, the `approx` feature must be added to the `ndarray` dependency in `Cargo.toml`. For example, `ndarray = { version = "0.13", features = ["approx"] }`.

This recipe also contains additional ownership examples. Here, `let z = a + b` consumes `a` and `b`, updates `a` with the result, then moves ownership to `z`. Alternatively, `let w = &c + &d` creates a new vector without consuming `c` or `d`, allowing their modification later. See [Binary Operators With Two Arrays](#) for additional detail.

```

#[macro_use(assert_abs_diff_eq)]
extern crate approx;
extern crate ndarray;

use ndarray::Array;

fn main() {
    let a = Array::from(vec![1., 2., 3., 4., 5.]);
    let b = Array::from(vec![5., 4., 3., 2., 1.]);
    let mut c = Array::from(vec![1., 2., 3., 4., 5.]);
    let mut d = Array::from(vec![5., 4., 3., 2., 1.]);

    let z = a + b;
    let w = &c + &d;

    assert_abs_diff_eq!(z, Array::from(vec![6., 6., 6., 6., 6.]));

    println!("c = {}", c);
    c[0] = 10.;
    d[1] = 10.;

    assert_abs_diff_eq!(w, Array::from(vec![6., 6., 6., 6., 6.]));
}

```

Vector norm

ndarray v0.13.0

This recipe demonstrates use of the `Array1` type, `ArrayView1` type, `fold` method, and `dot` method in computing the l_1 and l_2 norms of a given vector.

- The `l2_norm` function is the simpler of the two, as it computes the square root of the dot product of a vector with itself.
- The `l1_norm` function is computed by a `fold` operation that sums the absolute values of the elements. (This could also be performed with `x.mapv(f64::abs).scalar_sum()`, but that would allocate a new array for the result of the `mapv`.)

Note that both `l1_norm` and `l2_norm` take the `ArrayView1` type. This recipe considers vector norms, so the norm functions only need to accept one-dimensional views (hence `ArrayView1`). While the functions could take a parameter of type `&Array1<f64>` instead, that would require the caller to have a

reference to an owned array, which is more restrictive than just having access to a view (since a view can be created from any array or view, not just an owned array).

`Array` and `ArrayView` are both type aliases for `ArrayBase`. So, the most general argument type for the caller would be `&ArrayBase<S, Ix1>` where `S: Data`, because then the caller could use `&array` or `&view` instead of `x.view()`. If the function is part of a public API, that may be a better choice for the benefit of users. For internal functions, the more concise `ArrayView1<f64>` may be preferable.

```
#[macro_use(array)]
extern crate ndarray;

use ndarray::{Array1, ArrayView1};

fn l1_norm(x: ArrayView1<f64>) -> f64 {
    x.fold(0., |acc, elem| acc + elem.abs())
}

fn l2_norm(x: ArrayView1<f64>) -> f64 {
    x.dot(&x).sqrt()
}

fn normalize(mut x: Array1<f64>) -> Array1<f64> {
    let norm = l2_norm(x.view());
    x.mapv_inplace(|e| e/norm);
    x
}

fn main() {
    let x = array![1., 2., 3., 4., 5.];
    println!("||x||_2 = {}", l2_norm(x.view()));
    println!("||x||_1 = {}", l1_norm(x.view()));
    println!("Normalizing x yields {:?}", normalize(x));
}
```

Invert matrix

nalgebra v0.19.0 Science

Creates a 3x3 matrix with `nalgebra::Matrix3` and inverts it, if possible.

```
extern crate nalgebra;

use nalgebra::Matrix3;

fn main() {
    let m1 = Matrix3::new(2.0, 1.0, 1.0, 3.0, 2.0, 1.0, 2.0, 1.0, 2.0);
    println!("m1 = {}", m1);
    match m1.try_inverse() {
        Some(inv) => {
            println!("The inverse of m1 is: {}", inv);
        }
        None => {
            println!("m1 is not invertible!");
        }
    }
}
```

Trigonometry

Calculating the side length of a triangle

std 1.29.1 Science

Calculates the length of the hypotenuse of a right-angle triangle with an angle of 2 radians and opposite side length of 80.

```
fn main() {
    let angle: f64 = 2.0;
    let side_length = 80.0;

    let hypotenuse = side_length / angle.sin();

    println!("Hypotenuse: {}", hypotenuse);
}
```

Verifying tan is equal to sin divided by cos

std 1.29.1 Science

Verifies $\tan(x)$ is equal to $\sin(x)/\cos(x)$ for $x = 6$.

```
fn main() {  
    let x: f64 = 6.0;  
  
    let a = x.tan();  
    let b = x.sin() / x.cos();  
  
    assert_eq!(a, b);  
}
```

Distance between two points on the Earth

std 1.29.1

By default, Rust provides mathematical [float methods](#) such as trigonometric functions, square root, conversion functions between radians and degrees, and so forth.

The following example computes the distance in kilometers between two points on the Earth with the [Haversine formula](#). Points are expressed as pairs of latitude and longitude in degrees. Then, [to_radians](#) converts them in radian. [sin](#), [cos](#), [powi](#) and [sqrt](#) compute the central angle. Finally, it's possible to calculate the distance.

```
fn main() {
    let earth_radius_kilometer = 6371.0_f64;
    let (paris_latitude_degrees, paris_longitude_degrees) =
(48.85341_f64, -2.34880_f64);
    let (london_latitude_degrees, london_longitude_degrees) =
(51.50853_f64, -0.12574_f64);

    let paris_latitude = paris_latitude_degrees.to_radians();
    let london_latitude = london_latitude_degrees.to_radians();

    let delta_latitude = (paris_latitude_degrees -
london_latitude_degrees).to_radians();
    let delta_longitude = (paris_longitude_degrees -
london_longitude_degrees).to_radians();

    let central_angle_inner = (delta_latitude / 2.0).sin().powi(2)
+ paris_latitude.cos() * london_latitude.cos() *
(delta_longitude / 2.0).sin().powi(2);
    let central_angle = 2.0 * central_angle_inner.sqrt().asin();

    let distance = earth_radius_kilometer * central_angle;

    println!(
        "Distance between Paris and London on the surface of Earth is
{:.1} kilometers",
        distance
    );
}
```

Complex numbers

Creating complex numbers

num v0.2.1 Science

Creates complex numbers of type `num::complex::Complex`. Both the real and imaginary part of the complex number must be of the same type.

```
extern crate num;

fn main() {
    let complex_integer = num::complex::Complex::new(10, 20);
    let complex_float = num::complex::Complex::new(10.1, 20.1);

    println!("Complex integer: {}", complex_integer);
    println!("Complex float: {}", complex_float);
}
```

Adding complex numbers

num v0.2.1 Science

Performing mathematical operations on complex numbers is the same as on built in types: the numbers in question must be of the same type (i.e. floats or integers).

```
extern crate num;

fn main() {
    let complex_num1 = num::complex::Complex::new(10.0, 20.0); // Must
    use floats
    let complex_num2 = num::complex::Complex::new(3.1, -4.2);

    let sum = complex_num1 + complex_num2;

    println!("Sum: {}", sum);
}
```

Mathematical functions

num v0.2.1 Science

Complex numbers have a range of interesting properties when it comes to how they interact with other mathematical functions, most notably the family of sine functions as well as the number e . To use these functions with complex numbers, the `Complex` type has a few built in functions, all of which can be found here:

[num::complex::Complex](#) .

```
extern crate num;

use std::f64::consts::PI;
use num::complex::Complex;

fn main() {
    let x = Complex::new(0.0, 2.0*PI);

    println!("e^(2i * pi) = {}", x.exp()); // =~1
}
```

Statistics

Measures of central tendency

std 1.29.1 Science

These examples calculate measures of central tendency for a data set contained within a Rust array. There may be no mean, median or mode to calculate for an empty set of data, so each function returns an `[option]` to be handled by the caller.

The first example calculates the mean (the sum of all measurements divided by the number of measurements in the set) by producing an iterator of references over the data, and using `[sum]` and `[len]` to determine the total value and count of values respectively.

```
fn main() {
    let data = [3, 1, 6, 1, 5, 8, 1, 8, 10, 11];

    let sum = data.iter().sum::<i32>() as f32;
    let count = data.len();

    let mean = match count {
        positive if positive > 0 => Some(sum / count as f32),
        _ => None
    };

    println!("Mean of the data is {:?}", mean);
}
```

The second example calculates the median using the quickselect algorithm, which avoids a full `[sort]` by sorting only partitions of the data set known to possibly contain the median. This uses `[cmp]` and `[ordering]` to succinctly decide the next

partition to examine, and `[split_at]` to choose an arbitrary pivot for the next partition at each step.

```

use std::cmp::Ordering;

fn partition(data: &[i32]) -> Option<(Vec<i32>, i32, Vec<i32>)> {
    match data.len() {
        0 => None,
        _ => {
            let (pivot_slice, tail) = data.split_at(1);
            let pivot = pivot_slice[0];
            let (left, right) = tail.iter()
                .fold((vec![], vec![]), |mut splits, next| {
                    {
                        let (ref mut left, ref mut right) = &mut splits;
                        if next < &pivot {
                            left.push(*next);
                        } else {
                            right.push(*next);
                        }
                    }
                })
                .splits;
            Some((left, pivot, right))
        }
    }
}

fn select(data: &[i32], k: usize) -> Option<i32> {
    let part = partition(data);

    match part {
        None => None,
        Some((left, pivot, right)) => {
            let pivot_idx = left.len();

            match pivot_idx.cmp(&k) {
                Ordering::Equal => Some(pivot),
                Ordering::Greater => select(&left, k),
                Ordering::Less => select(&right, k - (pivot_idx + 1)),
            }
        },
    }
}

fn median(data: &[i32]) -> Option<f32> {
    let size = data.len();

    match size {
        even if even % 2 == 0 => {
            let fst_med = select(data, (even / 2) - 1);
            let snd_med = select(data, even / 2);
        }
    }
}

```

```

        match (fst_med, snd_med) {
            (Some(fst), Some(snd)) => Some((fst + snd) as f32 /
2.0),
            _ => None
        }
    },
    odd => select(data, odd / 2).map(|x| x as f32)
}
}

fn main() {
    let data = [3, 1, 6, 1, 5, 8, 1, 8, 10, 11];

    let part = partition(&data);
    println!("Partition is {:?}", part);

    let sel = select(&data, 5);
    println!("Selection at ordered index {} is {:?}", 5, sel);

    let med = median(&data);
    println!("Median is {:?}", med);
}

```

The final example calculates the mode using a mutable [`HashMap`] to collect counts of each distinct integer from the set, using a [`fold`] and the [`entry`] API. The most frequent value in the [`HashMap`] surfaces with [`max_by_key`].

```

use std::collections::HashMap;

fn main() {
    let data = [3, 1, 6, 1, 5, 8, 1, 8, 10, 11];

    let frequencies = data.iter().fold(HashMap::new(), |mut freqs,
value| {
        *freqs.entry(value).or_insert(0) += 1;
        freqs
    });

    let mode = frequencies
        .into_iter()
        .max_by_key(|&(_, count)| count)
        .map(|(value, _)| *value);

    println!("Mode of the data is {:?}", mode);
}

```

Standard deviation

std 1.29.1 Science

This example calculates the standard deviation and z-score of a set of measurements.

The standard deviation is defined as the square root of the variance (here calculated with f32's [`sqrt`], where the variance is the [`sum`] of the squared difference between each measurement and the [`mean`], divided by the number of measurements.

The z-score is the number of standard deviations a single measurement spans away from the [`mean`] of the data set.

```
fn mean(data: &[i32]) -> Option<f32> {
    let sum = data.iter().sum::<i32>() as f32;
    let count = data.len();

    match count {
        positive if positive > 0 => Some(sum / count as f32),
        _ => None,
    }
}

fn std_deviation(data: &[i32]) -> Option<f32> {
    match (mean(data), data.len()) {
        (Some(data_mean), count) if count > 0 => {
            let variance = data.iter().map(|value| {
                let diff = data_mean - (*value as f32);

                diff * diff
            }).sum::<f32>() / count as f32;

            Some(variance.sqrt())
        },
        _ => None
    }
}

fn main() {
    let data = [3, 1, 6, 1, 5, 8, 1, 8, 10, 11];

    let data_mean = mean(&data);
    println!("Mean is {:?}", data_mean);

    let data_std_deviation = std_deviation(&data);
    println!("Standard deviation is {:?}", data_std_deviation);

    let zscore = match (data_mean, data_std_deviation) {
        (Some(mean), Some(std_deviation)) => {
            let diff = data[4] as f32 - mean;

            Some(diff / std_deviation)
        },
        _ => None
    };
    println!("Z-score of data at index 4 (with value {}) is {:?}",
data[4], zscore);
}
```

Miscellaneous

Big integers

num v0.2.1 Science

Calculation for integers exceeding 128 bits are possible with `BigInt`.

```
extern crate num;

use num::bigint::{BigInt, ToBigInt};

fn factorial(x: i32) -> BigInt {
    if let Some(mut factorial) = 1.to_bigint() {
        for i in 1..(x+1) {
            factorial = factorial * i;
        }
        factorial
    }
    else {
        panic!("Failed to calculate factorial!");
    }
}

fn main() {
    println!("{}", 100, factorial(100));
}
```

Text Processing

| Recipe | Crates | Categories |
|---|------------------------------------|-----------------|
| Collect Unicode Graphemes | unicode-segmentation v1.6.0 | Encoding |
| Verify and extract login from an email address | regex v1.3.4 lazy_static v1.4.0 | Text processing |
| Extract a list of unique #Hashtags from a text | regex v1.3.4 lazy_static v1.4.0 | Text processing |
| Extract phone numbers from text | regex v1.3.4 | Text processing |
| Filter a log file by matching multiple regular expressions | regex v1.3.4 | Text processing |
| Replace all occurrences of one text pattern with another pattern. | regex v1.3.4 lazy_static v1.4.0 | Text processing |

| Recipe | Crates | Categories |
|--|------------|-----------------|
| Implement the <code>FromStr</code> trait for a custom struct | std 1.29.1 | Text processing |

Regular Expressions

Verify and extract login from an email address

regex v1.3.4 lazy_static v1.4.0 Text processing

Validates that an email address is formatted correctly, and extracts everything before the @ symbol.

```
#[macro_use]
extern crate lazy_static;
extern crate regex;

use regex::Regex;

fn extract_login(input: &str) -> Option<&str> {
    lazy_static! {
        static ref RE: Regex = Regex::new(r"(?x)
            ^(?P<login>[^\s]+)@
            ([[:word:]]+\.)*
            [[:word:]]+$
            ").unwrap();
    }
    RE.captures(input).and_then(|cap| {
        cap.name("login").map(|login| login.as_str())
    })
}

fn main() {
    assert_eq!(extract_login(r"I♥email@example.com"), Some(r"I♥email"));
    assert_eq!(
        extract_login(r"sdf+sdsfsd.as.sdsd@jhkk.d.rl"),
        Some(r"sdf+sdsfsd.as.sdsd")
    );
    assert_eq!(extract_login(r"More@Than@One@at.com"), None);
    assert_eq!(extract_login(r"Not an email@email"), None);
}
```

Extract a list of unique #Hashtags from a text

regex v1.3.4 lazy_static v1.4.0 Text processing

Extracts, sorts, and deduplicates list of hashtags from text.

The hashtag regex given here only catches Latin hashtags that start with a letter. The complete [twitter hashtag regex](#) is much more complicated.

```
extern crate regex;
#[macro_use]
extern crate lazy_static;

use regex::Regex;
use std::collections::HashSet;

fn extract_hashtags(text: &str) -> HashSet<&str> {
    lazy_static! {
        static ref HASHTAG_REGEX : Regex = Regex::new(
            r"\#[a-zA-Z][0-9a-zA-Z_]*"
        ).unwrap();
    }
    HASHTAG_REGEX.find_iter(text).map(|mat| mat.as_str()).collect()
}

fn main() {
    let tweet = "Hey #world, I just got my new #dog, say hello to Till.
#dog #forever #2 #_ ";
    let tags = extract_hashtags(tweet);
    assert!(tags.contains("#dog") && tags.contains("#forever") &&
tags.contains("#world"));
    assert_eq!(tags.len(), 3);
}
```

Extract phone numbers from text

regex v1.3.4 Text processing

Processes a string of text using `Regex::captures_iter` to capture multiple phone numbers. The example here is for US convention phone numbers.

```

extern crate regex;

use regex::Regex;
use std::fmt;

struct PhoneNumber<'a> {
    area: &'a str,
    exchange: &'a str,
    subscriber: &'a str,
}

impl<'a> fmt::Display for PhoneNumber<'a> {
    fn fmt(&self, f: &mut fmt::Formatter) -> fmt::Result {
        write!(f, "1 ({})-{}-{}", self.area, self.exchange,
self.subscriber)
    }
}

fn main() -> Result<()> {
    let phone_text = "
+1 505 881 9292 (v) +1 505 778 2212 (c) +1 505 881 9297 (f)
(202) 991 9534
Alex 5553920011
1 (800) 233-2010
1.299.339.1020";

    let re = Regex::new(
        r#"(?x)
        (?:\+?1)?           # Country Code Optional
        [\s\.]?
        (([2-9]\d{2})|(\([2-9]\d{2}\))) # Area Code
        [\s\.-]?
        ([2-9]\d{2})        # Exchange Code
        [\s\.-]?
        (\d{4})             # Subscriber Number"#,
    )?;

    let phone_numbers = re.captures_iter(phone_text).filter_map(|cap| {
        let groups = (cap.get(2).or(cap.get(3)), cap.get(4),
cap.get(5));
        match groups {
            (Some(area), Some(ext), Some(sub)) => Some(PhoneNumber {
                area: area.as_str(),
                exchange: ext.as_str(),
                subscriber: sub.as_str(),
            }),
            _ => None,
        }
    });
}

```

```
    assert_eq!(
        phone_numbers.map(|m| m.to_string()).collect::<Vec<_>>(),
        vec![
            "1 (505) 881-9292",
            "1 (505) 778-2212",
            "1 (505) 881-9297",
            "1 (202) 991-9534",
            "1 (555) 392-0011",
            "1 (800) 233-2010",
            "1 (299) 339-1020",
        ]
    );

    Ok(())
}
```

Filter a log file by matching multiple regular expressions

regex v1.3.4 Text processing

Reads a file named `application.log` and only outputs the lines containing “version X.X.X”, some IP address followed by port 443 (e.g. “192.168.0.1:443”), or a specific warning.

A `regex::RegexSetBuilder` composes a `regex::RegexSet`. Since backslashes are very common in regular expressions, using [raw string literals](#) makes them more readable.

```

extern crate regex;

use std::fs::File;
use std::io::{BufReader, BufRead};
use regex::RegexSetBuilder;

fn main() -> Result<()> {
    let log_path = "application.log";
    let buffered = BufReader::new(File::open(log_path)?);

    let set = RegexSetBuilder::new(&[
        r#"version "\d\.\d\.\d"#,
        r#"^\d{1,3}\.\d{1,3}\.\d{1,3}\.\d{1,3}:443"#,
        r#"warning.*timeout expired"#,
    ]).case_insensitive(true)
        .build()?;

    buffered
        .lines()
        .filter_map(|line| line.ok())
        .filter(|line| set.is_match(line.as_str()))
        .for_each(|x| println!("{}", x));

    Ok(())
}

```

Replace all occurrences of one text pattern with another pattern.

regex v1.3.4 lazy_static v1.4.0 Text processing

Replaces all occurrences of the standard ISO 8601 *YYYY-MM-DD* date pattern with the equivalent American English date with slashes. For example `2013-01-15` becomes `01/15/2013`.

The method `Regex::replace_all` replaces all occurrences of the whole regex. `&str` implements the `Replacer` trait which allows variables like `$abcde` to refer to corresponding named capture groups `(?P<abcde>REGEX)` from the search regex. See the [replacement string syntax](#) for examples and escaping detail.

```
extern crate regex;
#[macro_use]
extern crate lazy_static;

use std::borrow::Cow;
use regex::Regex;

fn reformat_dates(before: &str) -> Cow<str> {
    lazy_static! {
        static ref ISO8601_DATE_REGEX : Regex = Regex::new(
            r"(?P<y>\d{4})-(?P<m>\d{2})-(?P<d>\d{2})"
        ).unwrap();
    }
    ISO8601_DATE_REGEX.replace_all(before, "$m/$d/$y")
}

fn main() {
    let before = "2012-03-14, 2013-01-15 and 2014-07-05";
    let after = reformat_dates(before);
    assert_eq!(after, "03/14/2012, 01/15/2013 and 07/05/2014");
}
```

String Parsing

Collect Unicode Graphemes

unicode-segmentation v1.6.0 Text processing

Collect individual Unicode graphemes from UTF-8 string using the `UnicodeSegmentation::graphemes` function from the `unicode-segmentation` crate.

```
#[macro_use]
extern crate unicode_segmentation;
use unicode_segmentation::UnicodeSegmentation;

fn main() {
    let name = "José Guimarães\r\n";
    let graphemes = UnicodeSegmentation::graphemes(name, true)
        .collect:::<Vec<&str>>();
    assert_eq!(graphemes[3], "é");
}
```

Implement the `FromStr` trait for a custom struct

std 1.29.1 Text processing

Creates a custom struct `RGB` and implements the `FromStr` trait to convert a provided color hex code into its RGB color code.

```
use std::str::FromStr;

#[derive(Debug, PartialEq)]
struct RGB {
    r: u8,
    g: u8,
    b: u8,
}

impl FromStr for RGB {
    type Err = std::num::ParseIntError;

    // Parses a color hex code of the form '#rRgGbB..' into an
    // instance of 'RGB'
    fn from_str(hex_code: &str) -> Result<Self, Self::Err> {

        // u8::from_str_radix(src: &str, radix: u32) converts a string
        // slice in a given base to u8
        let r: u8 = u8::from_str_radix(&hex_code[1..3], 16)?;
        let g: u8 = u8::from_str_radix(&hex_code[3..5], 16)?;
        let b: u8 = u8::from_str_radix(&hex_code[5..7], 16)?;

        Ok(RGB { r, g, b })
    }
}

fn main() {
    let code: &str = &r"#fa7268";
    match RGB::from_str(code) {
        Ok(rgb) => {
            println!(
                r"The RGB color code is: R: {} G: {} B: {}",
                rgb.r, rgb.g, rgb.b
            );
        }
        Err(_) => {
            println!("{}", "is not a valid color hex code!", code);
        }
    }

    // test whether from_str performs as expected
    assert_eq!(
        RGB::from_str(&r"#fa7268").unwrap(),
        RGB {
            r: 250,
            g: 114,
            b: 104
        }
    );
}
```

Web Programming

Scraping Web Pages

| Recipe | Crates | Categories |
|--|--|------------|
| Extract all links from a webpage HTML | request v0.10.1 select v0.4.3 | Net |
| Check webpage for broken links | request v0.10.1 select v0.4.3 url v2.1.1 | Net |
| Extract all unique links from a MediaWiki markup | request v0.10.1 regex v1.3.4 | Net |

Uniform Resource Locations (URL)

| Recipe | Crates | Categories |
|--|------------|------------|
| Parse a URL from a string to a <code>url</code> type | url v2.1.1 | Net |
| Create a base URL by removing path segments | url v2.1.1 | Net |
| Create new URLs from a base URL | url v2.1.1 | Net |
| Extract the URL origin (scheme / host / port) | url v2.1.1 | Net |
| Remove fragment identifiers and query pairs from a URL | url v2.1.1 | Net |

Media Types (MIME)

| Recipe | Crates | Categories |
|-----------------------------|-------------|------------|
| Get MIME type from string | mime v1.1.3 | Encoding |
| Get MIME type from filename | mime v1.1.3 | Encoding |

| Recipe | Crates | Categories |
|--|--------------------------------|-----------------|
| Parse the MIME type of a HTTP response | mime v1.1.3 request v0.10.1 | Net Encoding |

Clients

| Recipe | Crates | Categories |
|---|-----------------------------------|-------------------|
| Make a HTTP GET request | request v0.10.1 | Net |
| Query the GitHub API | request v0.10.1 serde v1.0.104 | Net Encoding |
| Check if an API resource exists | request v0.10.1 | Net |
| Create and delete Gist with GitHub API | request v0.10.1 serde v1.0.104 | Net Encoding |
| Consume a paginated RESTful API | request v0.10.1 serde v1.0.104 | Net Encoding |
| Download a file to a temporary directory | request v0.10.1 tempdir v0.3.7 | Net Filesystem |
| Make a partial download with HTTP range headers | request v0.10.1 | Net |
| POST a file to paste-rs | request v0.10.1 | Net |

Extracting Links

Extract all links from a webpage HTML

request v0.10.1 select v0.4.3 Net

Use `request::get` to perform a HTTP GET request and then use `Document::from_read` to parse the response into a HTML document. `find` with the criteria of `Name` is "a" retrieves all links. Call `filter_map` on the `Selection` retrieves URLs from links that have the "href" `attr` (attribute).

```
extern crate reqwest;
extern crate select;

use select::document::Document;
use select::predicate::Name;

fn main() -> Result<()> {
    let res = reqwest::get("https://www.rust-lang.org/en-US/");

    Document::from_read(res)?
        .find(Name("a"))
        .filter_map(|n| n.attr("href"))
        .for_each(|x| println!("{}", x));

    Ok(())
}
```

Check a webpage for broken links

reqwest v0.10.1 select v0.4.3 url v2.1.1 Net

Call `get_base_url` to retrieve the base URL. If the document has a base tag, get the href `attr` from base tag. `Position::BeforePath` of the original URL acts as a default.

Iterate through links in the document and parse with `url::ParseOptions` and `Url::parse`). Makes a request to the links with reqwest and verifies `StatusCode` .

```

extern crate reqwest;
extern crate select;
extern crate url;

use std::collections::HashSet;

use url::{Url, Position};
use reqwest::StatusCode;
use select::document::Document;
use select::predicate::Name;

fn get_base_url(url: &Url, doc: &Document) -> Result<Url> {
    let base_tag_href = doc.find(Name("base")).filter_map(|n|
n.attr("href")).nth(0);

    let base_url = base_tag_href.map_or_else(
        || Url::parse(&url[..Position::BeforePath]),
        Url::parse,
    )?;

    Ok(base_url)
}

fn check_link(url: &Url) -> Result<bool> {
    let res = reqwest::get(url.as_ref())?;

    Ok(res.status() != StatusCode::NOT_FOUND)
}

fn main() -> Result<()> {
    let url = Url::parse("https://www.rust-lang.org/en-US/")?;

    let res = reqwest::get(url.as_ref())?;
    let document = Document::from_read(res)?;

    let base_url = get_base_url(&url, &document)?;

    let base_parser = Url::options().base_url(Some(&base_url));

    let links: HashSet<Url> = document
        .find(Name("a"))
        .filter_map(|n| n.attr("href"))
        .filter_map(|link| base_parser.parse(link).ok())
        .collect();

    links
        .iter()
        .filter(|link| check_link(link).ok() == Some(false))
        .for_each(|x| println!("{}", x));
}

```

```
    Ok(())  
}
```

Extract all unique links from a MediaWiki markup

request v0.10.1 regex v1.3.4 Net

Pull the source of a MediaWiki page using `request::get` and then look for all entries of internal and external links with `Regex::captures_iter`. Using `Cow` avoids excessive `String` allocations.

MediaWiki link syntax is described [here](#).

```

#[macro_use]
extern crate lazy_static;
extern crate reqwest;
extern crate regex;

use std::io::Read;
use std::collections::HashSet;
use std::borrow::Cow;
use regex::Regex;

fn extract_links(content: &str) -> Result<HashSet<Cow<str>>> {
    lazy_static! {
        static ref WIKI_REGEX: Regex =
            Regex::new(r"(?x)
links
                \[\[(?P<internal>[^\[\]]*)[^\[\]]*\]\] # internal
                |
links
                (url=|URL\|\|\[ ](?P<external>http.*?) [ \]} # external
            ").unwrap();
    }

    let links: HashSet<_> = WIKI_REGEX
        .captures_iter(content)
        .map(|c| match (c.name("internal"), c.name("external")) {
            (Some(val), None) => Cow::from(val.as_str().to_lowercase()),
            (None, Some(val)) => Cow::from(val.as_str()),
            _ => unreachable!(),
        })
        .collect();

    Ok(links)
}

fn main() -> Result<()> {
    let mut content = String::new();
    reqwest::get(
        "https://en.wikipedia.org
/w/index.php?title=Rust_(programming_language)&action=raw",
    )?
        .read_to_string(&mut content)?;

    println!("{:#?}", extract_links(&content));

    Ok(())
}

```

Uniform Resource Location

Parse a URL from a string to a `Url` type

url v2.1.1 Net

The `parse` method from the `url` crate validates and parses a `&str` into a `Url` struct. The input string may be malformed so this method returns `Result<Url, ParseError>`.

Once the URL has been parsed, it can be used with all of the methods in the `url` type.

```
extern crate url;

use url::{Url, ParseError};

fn main() -> Result<(), ParseError> {
    let s = "https://github.com/rust-lang/rust/issues?labels=E-easy&state=open";

    let parsed = Url::parse(s)?;
    println!("The path part of the URL is: {}", parsed.path());

    Ok(())
}
```

Create a base URL by removing path segments

url v2.1.1 Net

A base URL includes a protocol and a domain. Base URLs have no folders, files or query strings. Each of those items are stripped out of the given URL.

`PathSegmentsMut::clear` removes paths and `Url::set_query` removes query string.

```
extern crate url;

use url::Url;

fn main() -> Result<()> {
    let full = "https://github.com/rust-lang/cargo?asdf";

    let url = Url::parse(full)?;
    let base = base_url(url)?;

    assert_eq!(base.as_str(), "https://github.com/");
    println!("The base of the URL is: {}", base);

    Ok(())
}

fn base_url(mut url: Url) -> Result<Url> {
    match url.path_segments_mut() {
        Ok(mut path) => {
            path.clear();
        }
        Err(_) => {
            return Err(Error::from_kind(ErrorKind::CannotBeABase));
        }
    }

    url.set_query(None);

    Ok(url)
}
```

Create new URLs from a base URL

url v2.1.1 Net

The `join` method creates a new URL from a base and relative path.

```
extern crate url;

use url::{Url, ParseError};

fn main() -> Result<(), ParseError> {
    let path = "/rust-lang/cargo";

    let gh = build_github_url(path)?;

    assert_eq!(gh.as_str(), "https://github.com/rust-lang/cargo");
    println!("The joined URL is: {}", gh);

    Ok(())
}

fn build_github_url(path: &str) -> Result<Url, ParseError> {
    const GITHUB: &'static str = "https://github.com";

    let base = Url::parse(GITHUB).expect("hardcoded URL is known to be
valid");
    let joined = base.join(path)?;

    Ok(joined)
}
```

Extract the URL origin (scheme / host / port)

url v2.1.1 Net

The `Url` struct exposes various methods to extract information about the URL it represents.

```
extern crate url;

use url::{Url, Host, ParseError};

fn main() -> Result<(), ParseError> {
    let s = "ftp://rust-lang.org/examples";

    let url = Url::parse(s)?;

    assert_eq!(url.scheme(), "ftp");
    assert_eq!(url.host(), Some(Host::Domain("rust-lang.org")));
    assert_eq!(url.port_or_known_default(), Some(21));
    println!("The origin is as expected!");

    Ok(())
}
```

`origin` produces the same result.

```
extern crate url;

use url::{Url, Origin, Host};

fn main() -> Result<()> {
    let s = "ftp://rust-lang.org/examples";

    let url = Url::parse(s)?;

    let expected_scheme = "ftp".to_owned();
    let expected_host = Host::Domain("rust-lang.org".to_owned());
    let expected_port = 21;
    let expected = Origin::Tuple(expected_scheme, expected_host,
expected_port);

    let origin = url.origin();
    assert_eq!(origin, expected);
    println!("The origin is as expected!");

    Ok(())
}
```

Remove fragment identifiers and query pairs from a URL

`url v2.1.1` `Net`

Parses `Url` and slices it with `url::Position` to strip unneeded URL parts.

```
extern crate url;

use url::{Url, Position, ParseError};

fn main() -> Result<(), ParseError> {
    let parsed = Url::parse("https://github.com/rust-lang/rust
/issues?labels=E-easy&state=open");
    let cleaned: &str = &parsed[..Position::AfterPath];
    println!("cleaned: {}", cleaned);
    Ok(())
}
```

Media Types

Get MIME type from string

`mime v1.1.3` `Encoding`

The following example shows how to parse a `MIME` type from a string using the `mime` crate. `FromStrError` produces a default `MIME` type in an `unwrap_or` clause.

```
extern crate mime;
use mime::{Mime, APPLICATION_OCTET_STREAM};

fn main() {
    let invalid_mime_type = "i n v a l i d";
    let default_mime = invalid_mime_type
        .parse::<Mime>()
        .unwrap_or(APPLICATION_OCTET_STREAM);

    println!(
        "MIME for {:?} used default value {:?}",
        invalid_mime_type, default_mime
    );

    let valid_mime_type = "TEXT/PLAIN";
    let parsed_mime = valid_mime_type
        .parse::<Mime>()
        .unwrap_or(APPLICATION_OCTET_STREAM);

    println!(
        "MIME for {:?} was parsed as {:?}",
        valid_mime_type, parsed_mime
    );
}
```

Get MIME type from filename

mime v1.1.3 Encoding

The following example shows how to return the correct MIME type from a given filename using the [mime](#) crate. The program will check for file extensions and match against a known list. The return value is `mime:Mime`.

```
extern crate mime;
use mime::Mime;

fn find_mimetype (filename : &String) -> Mime{

    let parts : Vec<&str> = filename.split('.').collect();

    let res = match parts.last() {
        Some(v) =>
            match *v {
                "png" => mime::IMAGE_PNG,
                "jpg" => mime::IMAGE_JPEG,
                "json" => mime::APPLICATION_JSON,
                &_ => mime::TEXT_PLAIN,
            },
        None => mime::TEXT_PLAIN,
    };
    return res;
}

fn main() {
    let filenames = vec!("foobar.jpg", "foo.bar", "foobar.png");
    for file in filenames {
        let mime = find_mimetype(&file.to_owned());
        println!("MIME for {}: {}", file, mime);
    }
}
```

Parse the MIME type of a HTTP response

request v0.10.1 mime v1.1.3 Net Encoding

When receiving a HTTP response from `request` the [MIME type](#) or media type may be found in the [Content-Type](#) header. `request::header::HeaderMap::get` retrieves the header as a `request::header::HeaderValue`, which can be converted to a string. The `mime` crate can then parse that, yielding a `mime::Mime` value.

The `mime` crate also defines some commonly used MIME types.

Note that the `request::header` module is exported from the `http` crate.

```

extern crate mime;
extern crate request;

use mime::Mime;
use std::str::FromStr;
use request::header::CONTENT_TYPE;

fn main() -> Result<()> {
    let response = request::get("https://www.rust-lang.org/logos/rust-
logo-32x32.png");
    let headers = response.headers();

    match headers.get(CONTENT_TYPE) {
        None => {
            println!("The response does not contain a Content-Type
header.");
        }
        Some(content_type) => {
            let content_type = Mime::from_str(content_type.to_str())?;
            let media_type = match (content_type.type_(),
content_type.subtype()) {
                (mime::TEXT, mime::HTML) => "a HTML document",
                (mime::TEXT, _) => "a text document",
                (mime::IMAGE, mime::PNG) => "a PNG image",
                (mime::IMAGE, _) => "an image",
                _ => "neither text nor image",
            };

            println!("The reponse contains {}.\"", media_type);
        }
    };

    Ok(())
}

```

Clients

| Recipe | Crates | Categories |
|---------------------------------|-----------------------------------|-----------------|
| Make a HTTP GET request | request v0.10.1 | Net |
| Query the GitHub API | request v0.10.1 serde v1.0.104 | Net Encoding |
| Check if an API resource exists | request v0.10.1 | Net |

| Recipe | Crates | Categories |
|---|-----------------------------------|-------------------|
| Create and delete Gist with GitHub API | request v0.10.1 serde v1.0.104 | Net Encoding |
| Consume a paginated RESTful API | request v0.10.1 serde v1.0.104 | Net Encoding |
| Download a file to a temporary directory | request v0.10.1 tempdir v0.3.7 | Net Filesystem |
| Make a partial download with HTTP range headers | request v0.10.1 | Net |
| POST a file to paste-rs | request v0.10.1 | Net |

Making Requests

Make a HTTP GET request

request v0.10.1 Net

Parses the supplied URL and makes a synchronous HTTP GET request with `request::get`. Prints obtained `request::Response` status and headers. Reads HTTP response body into an allocated `String` using `read_to_string`.

```
extern crate request;

use std::io::Read;

fn main() -> Result<()> {
    let mut res = request::get("http://httpbin.org/get")?;
    let mut body = String::new();
    res.read_to_string(&mut body)?;

    println!("Status: {}", res.status());
    println!("Headers:\n{:#?}", res.headers());
    println!("Body:\n{}", body);

    Ok(())
}
```

Calling a Web API

Query the GitHub API

request v0.10.1 serde v1.0.104 Net Encoding

Queries GitHub [stargazers API v3](#) with `request::get` to get list of all users who have marked a GitHub project with a star. `request::Response` is deserialized with `Response::json` into `User` objects implementing `serde::Deserialize`.

```
#[macro_use]
extern crate serde;
extern crate serde_derive;
extern crate request;
use request::Error;

#[derive(Deserialize, Debug)]
struct User {
    login: String,
    id: u32,
}

fn main() -> Result<(), Error> {
    let request_url = format!("https://api.github.com/repos/{owner}/
/{repo}/stargazers",
                                owner = "rust-lang-nursery",
                                repo = "rust-cookbook");
    println!("{}", request_url);
    let mut response = request::get(&request_url)?;

    let users: Vec<User> = response.json()?;
    println!("{:?}", users);
    Ok(())
}
```

Check if an API resource exists

request v0.10.1 Net

Query the GitHub Users Endpoint using a HEAD request (`Client::head`) and then

inspect the response code to determine success. This is a quick way to query a rest resource without needing to receive a body. `request::Client` configured with `ClientBuilder::timeout` ensures a request will not last longer than a timeout.

```
extern crate request;

use request::Error;
use std::time::Duration;
use request::ClientBuilder;

fn main() -> Result<(), Error> {
    let user = "ferris-the-crab";
    let request_url = format!("https://api.github.com/users/{}", user);
    println!("{}", request_url);

    let timeout = Duration::new(5, 0);
    let client = ClientBuilder::new().timeout(timeout).build()?;
    let response = client.head(&request_url).send()?;

    if response.status().is_success() {
        println!("{}", user);
    } else {
        println!("{}", user);
    }

    Ok(())
}
```

Create and delete Gist with GitHub API

request v0.10.1 serde v1.0.104 Net Encoding

Creates a gist with POST request to GitHub [gists API v3](#) using `client::post` and removes it with DELETE request using `Client::delete`.

The `request::Client` is responsible for details of both requests including URL, body and authentication. The POST body from `serde_json::json!` macro provides arbitrary JSON body. Call to `RequestBuilder::json` sets the request body. `RequestBuilder::basic_auth` handles authentication. The call to `RequestBuilder::send` synchronously executes the requests.

```
extern crate request;
#[macro_use]
extern crate serde_derive;
#[macro_use]
extern crate serde_json;

use std::env;
use request::Client;

#[derive(Deserialize, Debug)]
struct Gist {
    id: String,
    html_url: String,
}

fn main() -> Result<()> {
    let gh_user = env::var("GH_USER")?;
    let gh_pass = env::var("GH_PASS")?;

    let gist_body = json!({
        "description": "the description for this gist",
        "public": true,
        "files": {
            "main.rs": {
                "content": r#"fn main() { println!("hello world!");}"#
            }
        }
    });

    let request_url = "https://api.github.com/gists";
    let mut response = Client::new()
        .post(request_url)
        .basic_auth(gh_user.clone(), Some(gh_pass.clone()))
        .json(&gist_body)
        .send()?;

    let gist: Gist = response.json()?;
    println!("Created {:?}", gist);

    let request_url = format!("{}/{}", request_url, gist.id);
    let response = Client::new()
        .delete(&request_url)
        .basic_auth(gh_user, Some(gh_pass))
        .send()?;

    println!("Gist {} deleted! Status code: {}", gist.id,
response.status());
    Ok(())
}
```

The example uses [HTTP Basic Auth](#) in order to authorize access to [GitHub API](#). Typical use case would employ one of the much more complex [OAuth](#) authorization flows.

Consume a paginated RESTful API

reqwest v0.10.1 serde v1.0.104 Net Encoding

Wraps a paginated web API in a convenient Rust iterator. The iterator lazily fetches the next page of results from the remote server as it arrives at the end of each page.

```
#[macro_use]
extern crate serde_derive;
extern crate reqwest;
use reqwest::Error;

#[derive(Deserialize)]
struct ApiResponse {
    dependencies: Vec<Dependency>,
    meta: Meta,
}

#[derive(Deserialize)]
struct Dependency {
    crate_id: String,
}

#[derive(Deserialize)]
struct Meta {
    total: u32,
}

struct ReverseDependencies {
    crate_id: String,
    dependencies: <Vec<Dependency> as IntoIterator>::IntoIter,
    client: reqwest::Client,
    page: u32,
    per_page: u32,
    total: u32,
}

impl ReverseDependencies {
    fn of(crate_id: &str) -> Result<Self, Error> {
        Ok(ReverseDependencies {
            crate_id: crate_id.to_owned(),
            dependencies: vec![].into_iter(),
            client: reqwest::Client::new(),
            page: 0,
            per_page: 100,
            total: 0,
        })
    }

    fn try_next(&mut self) -> Result<Option<Dependency>, Error> {
        if let Some(dep) = self.dependencies.next() {
            return Ok(Some(dep));
        }

        if self.page > 0 && self.page * self.per_page >= self.total {
            return Ok(None);
        }
    }
}
```

```

        self.page += 1;
        let url = format!("https://crates.io/api/v1/crates
/{}/reverse_dependencies?page={}&per_page={}",
                        self.crate_id,
                        self.page,
                        self.per_page);

        let response = self.client.get(&url).send()?.json:::
<ApiResponse>()?;
        self.dependencies = response.dependencies.into_iter();
        self.total = response.meta.total;
        Ok(self.dependencies.next())
    }
}

impl Iterator for ReverseDependencies {
    type Item = Result<Dependency, Error>;

    fn next(&mut self) -> Option<Self::Item> {
        match self.try_next() {
            Ok(Some(dep)) => Some(Ok(dep)),
            Ok(None) => None,
            Err(err) => Some(Err(err)),
        }
    }
}

fn main() -> Result<(), Error> {
    for dep in ReverseDependencies::of("serde")? {
        println!("reverse dependency: {}", dep?.crate_id);
    }
    Ok(())
}

```

Downloads

Download a file to a temporary directory

request v0.10.1 tempdir v0.3.7 Net Filesystem

Creates a temporary directory with `tempfile::Builder` and synchronously downloads a file over HTTP using `request::get`.

Creates a target `File` with name obtained from `Response::url` within `tempdir()` and copies downloaded data into it with `io::copy`. The temporary directory is automatically removed on `run` function return.

```
extern crate request;
extern crate tempfile;

use std::io::copy;
use std::fs::File;
use tempfile::Builder;

fn main() -> Result<()> {
    let tmp_dir = Builder::new().prefix("example").tempdir()?;
    let target = "https://www.rust-lang.org/logos/rust-
logo-512x512.png";
    let mut response = request::get(target)?;

    let mut dest = {
        let fname = response
            .url()
            .path_segments()
            .and_then(|segments| segments.last())
            .and_then(|name| if name.is_empty() { None } else {
                Some(name) })
            .unwrap_or("tmp.bin");

        println!("file to download: '{}'", fname);
        let fname = tmp_dir.path().join(fname);
        println!("will be located under: '{}:?''", fname);
        File::create(fname)?
    };
    copy(&mut response, &mut dest)?;
    Ok(())
}
```

POST a file to paste-rs

request v0.10.1 Net

`request::Client` establishes a connection to `https://paste.rs` following the `request::RequestBuilder` pattern. Calling `Client::post` with a URL establishes the destination, `RequestBuilder::body` sets the content to send by reading the file, and `RequestBuilder::send` blocks until the file uploads and the response returns. `read_to_string` returns the response and displays in the console.

```
extern crate request;

use std::fs::File;
use std::io::Read;
use request::Client;

fn main() -> Result<()> {
    let paste_api = "https://paste.rs";
    let file = File::open("message"?);

    let mut response = Client::new().post(paste_api).body(file).send()?;
    let mut response_body = String::new();
    response.read_to_string(&mut response_body)?;
    println!("Your paste is located at: {}", response_body);
    Ok(())
}
```

Make a partial download with HTTP range headers

request v0.10.1 Net

Uses `request::Client::head` to get the `Content-Length` of the response.

The code then uses `request::Client::get` to download the content in chunks of 10240 bytes, while printing progress messages. The `Range` header specifies the chunk size and position.

The Range header is defined in [RFC7233](#).

```
extern crate request;

use std::fs::File;
use std::str::FromStr;
use request::header::{HeaderValue, CONTENT_LENGTH, RANGE};
use request::StatusCode;

fn main() -> Result<()> {
    let url = "https://httpbin.org/range/102400?duration=2";
    const CHUNK_SIZE: u32 = 10240;

    let client = request::Client::new();
    let response = client.head(url).send()?;
    let length = response
        .headers()
        .get(CONTENT_LENGTH)
        .ok_or("response doesn't include the content length")?;
    let length = u64::from_str(length.to_str())?.map_err(|_| "invalid
Content-Length header")?;

    let mut output_file = File::create("download.bin")?;

    println!("starting download...");
    for range in PartialRangeIter::new(0, length - 1, CHUNK_SIZE)? {
        println!("range {:?}", range);
        let mut response = client.get(url).header(RANGE, range).send()?;

        let status = response.status();
        if !(status == StatusCode::OK || status ==
StatusCode::PARTIAL_CONTENT) {
            bail!("Unexpected server response: {}", status)
        }

        std::io::copy(&mut response, &mut output_file)?;
    }

    println!("Finished with success!");
    Ok(())
}
```